

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2019

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	11	3,480	1,922	11	69	57	5	72	255	38	2	3	26	0
	Flex	.18	.00	.02	.18	.42	.56	1.33	.28	1.36	.78	1.51	.80	1.13	0.00
	Rigid	.38	.01	.02	.24	.43	.98	3.51	.30	2.50	2.01	1.83	1.37	1.72	0.00
	GVW	10.5	5.6	9.7	12.8	19.2	32.3	76.0	24.8	64.6	79.7	54.0	60.6	71.9	0.0
N	Num	9	1,669	974	2	34	29	4	39	133	21	1	2	12	0
	Flex	.11	.00	.02	.68	.42	.53	1.22	.31	1.37	.82	.28	.68	.85	0.00
	Rigid	.24	.00	.02	.95	.42	.92	3.17	.34	2.57	2.17	.61	1.36	1.27	0.00
	GVW	7.9	5.3	9.3	30.6	18.5	30.4	72.2	24.9	63.5	79.3	32.8	57.3	60.9	0.0
S	Num	3	1,810	947	10	35	28	2	33	122	17	1	1	13	0
	Flex	.40	.01	.02	.09	.44	.56	.98	.25	1.38	.77	2.53	.63	1.35	0.00
	Rigid	.86	.01	.02	.13	.44	1.02	2.65	.27	2.47	1.93	2.50	.68	2.07	0.00
	GVW	20.9	5.8	10.0	10.7	19.9	34.0	70.2	24.8	65.9	79.5	69.9	56.3	81.2	0.0
N Lane1	Num	9	1,669	974	2	34	29	4	39	133	21	1	2	12	0
	Flex	.11	.00	.02	.68	.42	.53	1.22	.31	1.37	.82	.28	.68	.85	0.00
	Rigid	.24	.00	.02	.95	.42	.92	3.17	.34	2.57	2.17	.61	1.36	1.27	0.00
	GVW	7.9	5.3	9.3	30.6	18.5	30.4	72.2	24.9	63.5	79.3	32.8	57.3	60.9	0.0
S Lane1	Num	3	1,810	947	10	35	28	2	33	122	17	1	1	13	0
	Flex	.40	.01	.02	.09	.44	.56	.98	.25	1.38	.77	2.53	.63	1.35	0.00
	Rigid	.86	.01	.02	.13	.44	1.02	2.65	.27	2.47	1.93	2.50	.68	2.07	0.00
	GVW	20.9	5.8	10.0	10.7	19.9	34.0	70.2	24.8	65.9	79.5	69.9	56.3	81.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2019

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9