

Idaho Transportation Department

Monthly WIM Distribution for Aug-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	7	3,770	2,155	21	79	64	5	80	287	50	2	6	31	0
	Flex	.04	.00	.02	.09	.38	.43	.56	.29	1.19	.68	1.13	.90	1.35	0.00
	Rigid	.08	.00	.02	.12	.38	.74	1.34	.32	2.14	1.79	1.35	1.35	1.96	0.00
	GVW	4.1	5.2	9.2	7.1	19.3	32.4	61.7	25.1	63.7	80.0	46.9	62.8	73.4	0.0
N	Num	7	1,839	1,072	2	40	31	4	41	155	26	1	4	15	0
	Flex	.02	.00	.02	.68	.36	.39	.54	.33	1.23	.63	.40	.74	1.30	0.00
	Rigid	.05	.00	.02	.89	.36	.70	1.25	.38	2.24	1.66	.64	1.24	1.70	0.00
	GVW	3.0	5.4	9.3	31.1	18.7	31.1	60.4	25.2	63.9	78.5	33.6	59.3	68.3	0.0
S	Num	2	1,931	1,083	19	39	33	1	39	131	24	1	3	16	0
	Flex	.16	.00	.02	.04	.40	.45	.93	.25	1.16	.73	2.51	1.01	1.40	0.00
	Rigid	.34	.00	.02	.05	.40	.76	2.38	.27	2.03	1.87	2.48	1.26	2.17	0.00
	GVW	14.0	5.0	9.1	5.1	20.0	33.4	73.9	25.1	63.4	80.8	69.2	65.7	77.7	0.0
N Lane1	Num	7	1,839	1,072	2	40	31	4	41	155	26	1	4	15	0
	Flex	.02	.00	.02	.68	.36	.39	.54	.33	1.23	.63	.40	.74	1.30	0.00
	Rigid	.05	.00	.02	.89	.36	.70	1.25	.38	2.24	1.66	.64	1.24	1.70	0.00
	GVW	3.0	5.4	9.3	31.1	18.7	31.1	60.4	25.2	63.9	78.5	33.6	59.3	68.3	0.0
S Lane1	Num	2	1,931	1,083	19	39	33	1	39	131	24	1	3	16	0
	Flex	.16	.00	.02	.04	.40	.45	.93	.25	1.16	.73	2.51	1.01	1.40	0.00
	Rigid	.34	.00	.02	.05	.40	.76	2.38	.27	2.03	1.87	2.48	1.26	2.17	0.00
	GVW	14.0	5.0	9.1	5.1	20.0	33.4	73.9	25.1	63.4	80.8	69.2	65.7	77.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9