

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	5	3,879	2,118	29	89	163	5	71	311	61	2	5	44	0
	Flex	.02	.01	.02	.09	.44	.42	.58	.22	1.14	.63	1.19	.64	1.09	0.00
	Rigid	.05	.01	.02	.11	.44	.76	1.45	.25	2.06	1.62	1.19	1.01	1.66	0.00
	GVW	6.7	5.3	9.4	6.9	19.9	32.0	58.9	24.5	63.0	76.2	48.5	60.7	71.3	0.0
N	Num	5	1,890	1,094	4	47	82	4	37	169	31	2	3	23	0
	Flex	.02	.00	.02	.58	.43	.52	.56	.17	1.18	.59	.15	.64	.91	0.00
	Rigid	.05	.00	.02	.72	.43	1.00	1.41	.18	2.16	1.53	.14	1.13	1.30	0.00
	GVW	6.3	5.3	9.5	23.3	19.9	34.8	58.8	23.5	64.2	76.9	34.7	62.6	65.4	0.0
S	Num	1	1,990	1,025	26	42	81	3	34	142	29	1	2	21	0
	Flex	.00	.01	.02	.04	.44	.31	.39	.28	1.11	.67	3.27	.57	1.25	0.00
	Rigid	.01	.01	.02	.05	.44	.52	1.08	.31	1.95	1.71	3.33	.72	2.00	0.00
	GVW	7.1	5.2	9.2	5.4	19.8	29.3	55.3	25.5	61.5	75.2	72.3	56.7	77.1	0.0
N Lane1	Num	5	1,890	1,094	4	47	82	4	37	169	31	2	3	23	0
	Flex	.02	.00	.02	.58	.43	.52	.56	.17	1.18	.59	.15	.64	.91	0.00
	Rigid	.05	.00	.02	.72	.43	1.00	1.41	.18	2.16	1.53	.14	1.13	1.30	0.00
	GVW	6.3	5.3	9.5	23.3	19.9	34.8	58.8	23.5	64.2	76.9	34.7	62.6	65.4	0.0
S Lane1	Num	1	1,990	1,025	26	42	81	3	34	142	29	1	2	21	0
	Flex	.00	.01	.02	.04	.44	.31	.39	.28	1.11	.67	3.27	.57	1.25	0.00
	Rigid	.01	.01	.02	.05	.44	.52	1.08	.31	1.95	1.71	3.33	.72	2.00	0.00
	GVW	7.1	5.2	9.2	5.4	19.8	29.3	55.3	25.5	61.5	75.2	72.3	56.7	77.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9