

Idaho Transportation Department

Monthly WIM Distribution for Oct-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	4	3,848	1,859	32	89	175	6	69	331	73	2	5	33	0
	Flex	.30	.01	.02	.10	.37	.38	.74	.21	1.11	.65	1.60	.85	1.33	0.00
	Rigid	.63	.01	.02	.11	.37	.69	1.95	.23	1.99	1.64	1.61	1.46	1.99	0.00
	GVW	21.3	5.8	9.2	7.7	18.9	30.9	70.0	23.8	62.5	75.9	54.6	64.1	75.5	0.0
N	Num	2	1,795	1,018	10	47	88	4	39	174	40	1	3	17	0
	Flex	.39	.00	.02	.25	.37	.37	.59	.17	1.15	.67	.35	.77	1.28	0.00
	Rigid	.82	.00	.02	.30	.37	.67	1.52	.18	2.10	1.71	.33	1.43	1.84	0.00
	GVW	23.2	5.4	9.3	11.0	19.0	31.1	67.1	23.1	65.0	80.1	42.5	63.5	71.6	0.0
S	Num	3	2,053	841	22	42	87	2	30	157	33	1	2	16	0
	Flex	.17	.02	.02	.04	.36	.40	1.10	.27	1.06	.63	2.89	.81	1.38	0.00
	Rigid	.36	.02	.02	.04	.36	.71	3.11	.29	1.87	1.52	2.91	1.13	2.14	0.00
	GVW	18.3	6.2	9.2	6.3	18.7	30.5	75.4	24.6	59.6	70.4	68.4	62.2	79.7	0.0
N Lane1	Num	2	1,795	1,018	10	47	88	4	39	174	40	1	3	17	0
	Flex	.39	.00	.02	.25	.37	.37	.59	.17	1.15	.67	.35	.77	1.28	0.00
	Rigid	.82	.00	.02	.30	.37	.67	1.52	.18	2.10	1.71	.33	1.43	1.84	0.00
	GVW	23.2	5.4	9.3	11.0	19.0	31.1	67.1	23.1	65.0	80.1	42.5	63.5	71.6	0.0
S Lane1	Num	3	2,053	841	22	42	87	2	30	157	33	1	2	16	0
	Flex	.17	.02	.02	.04	.36	.40	1.10	.27	1.06	.63	2.89	.81	1.38	0.00
	Rigid	.36	.02	.02	.04	.36	.71	3.11	.29	1.87	1.52	2.91	1.13	2.14	0.00
	GVW	18.3	6.2	9.2	6.3	18.7	30.5	75.4	24.6	59.6	70.4	68.4	62.2	79.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2019

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9