

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2019

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	3,703	1,531	14	73	61	5	53	256	44	2	3	14	0
	Flex	.54	.02	.02	5.51	3.51	2.85	2.57	2.09	7.93	5.00	9.00	7.48	6.18	0.00
	Rigid	1.28	.02	.02	7.83	4.14	5.29	7.44	2.65	15.71	13.47	10.30	16.04	10.34	0.00
	GVW	13.8	5.3	8.4	34.9	28.6	45.6	92.9	39.9	93.0	118.9	75.9	104.8	97.6	0.0
N	Num	2	1,697	884	8	39	30	3	29	137	21	1	2	8	0
	Flex	2.48	.01	.02	7.15	4.36	3.27	3.42	2.28	9.04	6.57	7.83	8.57	5.60	0.00
	Rigid	6.07	.01	.02	10.33	5.19	6.06	9.84	2.93	18.54	17.76	8.70	18.72	8.73	0.00
	GVW	27.3	5.1	8.6	44.2	31.6	51.8	104.1	40.9	100.8	131.3	80.7	115.1	95.9	0.0
S	Num	2	2,006	647	7	34	31	3	24	119	23	1	2	7	0
	Flex	.08	.03	.02	3.28	2.67	2.44	1.82	1.73	6.75	4.42	9.88	.97	6.15	0.00
	Rigid	.14	.03	.02	5.18	3.10	4.52	5.25	2.11	12.67	11.76	11.68	1.44	11.09	0.00
	GVW	9.9	5.5	8.0	28.4	25.3	40.8	82.8	37.6	84.5	113.3	71.3	58.0	98.7	0.0
N Lane1	Num	2	1,697	884	8	39	30	3	29	137	21	1	2	8	0
	Flex	2.48	.01	.02	7.15	4.36	3.27	3.42	2.28	9.04	6.57	7.83	8.57	5.60	0.00
	Rigid	6.07	.01	.02	10.33	5.19	6.06	9.84	2.93	18.54	17.76	8.70	18.72	8.73	0.00
	GVW	27.3	5.1	8.6	44.2	31.6	51.8	104.1	40.9	100.8	131.3	80.7	115.1	95.9	0.0
S Lane1	Num	2	2,006	647	7	34	31	3	24	119	23	1	2	7	0
	Flex	.08	.03	.02	3.28	2.67	2.44	1.82	1.73	6.75	4.42	9.88	.97	6.15	0.00
	Rigid	.14	.03	.02	5.18	3.10	4.52	5.25	2.11	12.67	11.76	11.68	1.44	11.09	0.00
	GVW	9.9	5.5	8.0	28.4	25.3	40.8	82.8	37.6	84.5	113.3	71.3	58.0	98.7	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2019

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9