

Idaho Transportation Department

Monthly WIM Distribution for Mar-2020

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	3,330	1,776	6	83	58	6	79	339	52	1	2	11	0
	Flex	.08	.00	.00	.63	.35	.38	.52	.29	1.08	.63	.73	.95	.80	0.00
	Rigid	.17	.00	.00	.74	.35	.67	1.42	.33	1.92	1.58	.72	2.00	1.39	0.00
	GVW	8.5	2.4	4.2	29.6	18.4	32.0	68.1	26.6	62.1	77.1	47.1	72.4	75.3	0.0
N	Num	1	1,546	939	3	40	26	5	40	186	28	1	2	6	0
	Flex	.18	.00	.00	.84	.29	.38	.50	.31	.99	.50	.43	.97	.99	0.00
	Rigid	.41	.00	.00	.95	.28	.68	1.38	.35	1.81	1.30	.41	2.04	1.75	0.00
	GVW	15.0	2.3	4.2	33.4	17.5	32.4	68.6	26.0	62.3	76.5	44.7	73.0	79.1	0.0
S	Num	2	1,784	837	3	43	31	2	38	153	25	1	2	5	0
	Flex	.02	.00	.00	.50	.41	.37	.60	.28	1.17	.76	6.31	.55	.63	0.00
	Rigid	.04	.00	.00	.62	.41	.63	1.57	.31	2.03	1.87	6.64	1.15	1.05	0.00
	GVW	5.4	2.5	4.2	28.3	19.2	31.2	66.8	27.2	61.6	77.7	89.8	58.8	71.9	0.0
N Lane1	Num	1	1,546	939	3	40	26	5	40	186	28	1	2	6	0
	Flex	.18	.00	.00	.84	.29	.38	.50	.31	.99	.50	.43	.97	.99	0.00
	Rigid	.41	.00	.00	.95	.28	.68	1.38	.35	1.81	1.30	.41	2.04	1.75	0.00
	GVW	15.0	2.3	4.2	33.4	17.5	32.4	68.6	26.0	62.3	76.5	44.7	73.0	79.1	0.0
S Lane1	Num	2	1,784	837	3	43	31	2	38	153	25	1	2	5	0
	Flex	.02	.00	.00	.50	.41	.37	.60	.28	1.17	.76	6.31	.55	.63	0.00
	Rigid	.04	.00	.00	.62	.41	.63	1.57	.31	2.03	1.87	6.64	1.15	1.05	0.00
	GVW	5.4	2.5	4.2	28.3	19.2	31.2	66.8	27.2	61.6	77.7	89.8	58.8	71.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2020

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9