

Idaho Transportation Department

Monthly WIM Distribution for Apr-2020

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3	2,862	1,799	4	74	55	5	77	301	49	1	4	16	0
	Flex	.10	.00	.00	.62	.30	.38	.36	.32	1.05	.62	.28	.68	.97	0.00
	Rigid	.21	.00	.00	.80	.30	.67	.97	.36	1.93	1.64	.27	1.24	1.58	0.00
	GVW	7.9	2.4	4.3	31.1	17.7	32.3	54.5	26.5	61.9	78.4	38.4	64.8	73.1	0.0
N	Num	2	1,343	934	2	36	25	4	39	157	28	1	3	7	0
	Flex	.14	.00	.00	.78	.30	.42	.45	.35	1.04	.60	.38	.69	1.25	0.00
	Rigid	.31	.00	.00	1.01	.30	.76	1.09	.40	1.94	1.62	.36	1.38	2.01	0.00
	GVW	9.9	2.5	4.4	37.7	17.7	33.5	59.1	26.5	62.4	80.5	46.6	66.9	74.8	0.0
S	Num	1	1,519	865	2	38	30	1	38	144	22	1	2	8	0
	Flex	.14	.00	.00	.42	.30	.37	.46	.29	1.06	.63	.23	.64	.70	0.00
	Rigid	.30	.00	.00	.52	.30	.61	1.32	.32	1.90	1.65	.22	.76	1.18	0.00
	GVW	11.2	2.4	4.2	22.4	17.7	31.7	57.2	26.6	61.2	76.6	34.3	58.6	71.0	0.0
N Lane1	Num	2	1,343	934	2	36	25	4	39	157	28	1	3	7	0
	Flex	.14	.00	.00	.78	.30	.42	.45	.35	1.04	.60	.38	.69	1.25	0.00
	Rigid	.31	.00	.00	1.01	.30	.76	1.09	.40	1.94	1.62	.36	1.38	2.01	0.00
	GVW	9.9	2.5	4.4	37.7	17.7	33.5	59.1	26.5	62.4	80.5	46.6	66.9	74.8	0.0
S Lane1	Num	1	1,519	865	2	38	30	1	38	144	22	1	2	8	0
	Flex	.14	.00	.00	.42	.30	.37	.46	.29	1.06	.63	.23	.64	.70	0.00
	Rigid	.30	.00	.00	.52	.30	.61	1.32	.32	1.90	1.65	.22	.76	1.18	0.00
	GVW	11.2	2.4	4.2	22.4	17.7	31.7	57.2	26.6	61.2	76.6	34.3	58.6	71.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2020

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9