

Idaho Transportation Department

Monthly WIM Distribution for May-2020

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	4	3,358	2,066	3	71	49	8	80	289	57	1	6	16	0
	Flex	.08	.00	.00	.43	.29	.32	.50	.25	1.01	.61	.41	.76	.89	0.00
	Rigid	.18	.00	.00	.59	.28	.56	1.42	.29	1.92	1.64	.39	1.31	1.39	0.00
	GVW	7.9	2.4	4.3	25.9	17.6	30.3	65.0	24.3	61.8	78.4	43.6	62.3	68.4	0.0
N	Num	5	1,598	1,052	2	35	22	6	41	148	31	1	4	8	0
	Flex	.02	.00	.00	.70	.25	.36	.47	.26	1.01	.65	.29	.65	1.09	0.00
	Rigid	.05	.00	.00	1.03	.25	.66	1.34	.31	1.93	1.76	.27	1.23	1.59	0.00
	GVW	4.5	2.5	4.4	33.9	16.8	31.0	63.6	24.2	61.4	80.9	42.0	60.3	67.1	0.0
S	Num	1	1,759	1,013	2	36	27	3	39	141	26	2	2	8	0
	Flex	.24	.00	.00	.32	.32	.29	.65	.24	1.01	.57	1.25	1.00	.64	0.00
	Rigid	.51	.00	.00	.41	.31	.48	1.78	.28	1.91	1.50	1.26	1.33	1.09	0.00
	GVW	14.4	2.4	4.3	21.0	18.3	29.9	72.5	24.5	62.1	75.5	52.2	66.5	67.6	0.0
N Lane1	Num	5	1,598	1,052	2	35	22	6	41	148	31	1	4	8	0
	Flex	.02	.00	.00	.70	.25	.36	.47	.26	1.01	.65	.29	.65	1.09	0.00
	Rigid	.05	.00	.00	1.03	.25	.66	1.34	.31	1.93	1.76	.27	1.23	1.59	0.00
	GVW	4.5	2.5	4.4	33.9	16.8	31.0	63.6	24.2	61.4	80.9	42.0	60.3	67.1	0.0
S Lane1	Num	1	1,759	1,013	2	36	27	3	39	141	26	2	2	8	0
	Flex	.24	.00	.00	.32	.32	.29	.65	.24	1.01	.57	1.25	1.00	.64	0.00
	Rigid	.51	.00	.00	.41	.31	.48	1.78	.28	1.91	1.50	1.26	1.33	1.09	0.00
	GVW	14.4	2.4	4.3	21.0	18.3	29.9	72.5	24.5	62.1	75.5	52.2	66.5	67.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2020

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9