

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2022

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	11	3,683	2,196	3	74	75	6	77	293	51	2	3	23	0
	Flex	.11	.00	.00	1.10	.59	.60	1.23	.36	1.54	1.06	1.36	2.10	1.83	0.00
	Rigid	.24	.00	.00	1.62	.60	1.08	3.08	.45	2.95	2.69	1.33	4.13	2.93	0.00
	GVW	5.1	3.0	5.2	38.9	21.2	34.8	74.1	26.9	67.0	85.2	55.3	80.6	80.4	0.0
N	Num	10	1,832	1,092	2	37	36	5	40	149	26	2	2	11	0
	Flex	.07	.00	.00	.96	.40	.52	.82	.20	1.22	.88	1.40	2.21	1.14	0.00
	Rigid	.15	.00	.00	1.45	.41	.92	1.91	.24	2.33	2.21	1.37	4.69	1.70	0.00
	GVW	3.9	2.7	4.6	39.9	18.9	31.4	67.4	23.3	61.8	79.9	56.1	83.5	63.6	0.0
S	Num	2	1,852	1,104	2	37	39	2	37	144	24	1	2	12	0
	Flex	.35	.00	.00	1.21	.78	.67	2.38	.54	1.87	1.25	1.04	1.49	2.42	0.00
	Rigid	.77	.00	.00	1.76	.80	1.22	6.22	.69	3.58	3.16	.98	2.23	4.01	0.00
	GVW	12.6	3.4	5.8	38.3	23.5	37.8	92.7	30.9	72.4	89.7	57.3	71.0	95.9	0.0
N Lane1	Num	10	1,832	1,092	2	37	36	5	40	149	26	2	2	11	0
	Flex	.07	.00	.00	.96	.40	.52	.82	.20	1.22	.88	1.40	2.21	1.14	0.00
	Rigid	.15	.00	.00	1.45	.41	.92	1.91	.24	2.33	2.21	1.37	4.69	1.70	0.00
	GVW	3.9	2.7	4.6	39.9	18.9	31.4	67.4	23.3	61.8	79.9	56.1	83.5	63.6	0.0
S Lane1	Num	2	1,852	1,104	2	37	39	2	37	144	24	1	2	12	0
	Flex	.35	.00	.00	1.21	.78	.67	2.38	.54	1.87	1.25	1.04	1.49	2.42	0.00
	Rigid	.77	.00	.00	1.76	.80	1.22	6.22	.69	3.58	3.16	.98	2.23	4.01	0.00
	GVW	12.6	3.4	5.8	38.3	23.5	37.8	92.7	30.9	72.4	89.7	57.3	71.0	95.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2022

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9