

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2022

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	3,805	2,293	6	94	105	4	75	370	91	1	2	26	0
	Flex	.13	.00	.00	.90	.54	.55	.98	.35	1.43	1.01	.50	1.68	1.48	0.00
	Rigid	.27	.00	.00	1.26	.55	.98	2.37	.43	2.75	2.51	.48	3.35	2.46	0.00
	GVW	6.9	2.8	5.0	36.9	20.6	33.6	66.7	26.8	65.8	81.7	37.4	79.1	75.6	0.0
N	Num	3	1,895	1,141	4	46	51	3	40	196	53	1	2	14	0
	Flex	.09	.00	.00	1.09	.39	.41	.73	.21	1.28	.80	.50	1.72	1.42	0.00
	Rigid	.19	.00	.00	1.54	.39	.74	1.59	.26	2.46	2.01	.48	3.56	2.16	0.00
	GVW	5.8	2.6	4.6	38.1	18.8	30.5	61.0	24.1	63.9	79.9	37.4	82.3	68.9	0.0
S	Num	2	1,910	1,152	3	49	54	2	36	174	38	0	1	12	0
	Flex	.13	.00	.00	.87	.68	.67	1.69	.50	1.59	1.25	0.00	.87	1.43	0.00
	Rigid	.28	.00	.00	1.18	.69	1.23	4.19	.63	3.07	3.04	0.00	1.35	2.57	0.00
	GVW	7.5	3.1	5.4	34.6	22.3	36.6	76.9	29.7	67.7	83.4	0.0	57.2	81.4	0.0
N Lane1	Num	3	1,895	1,141	4	46	51	3	40	196	53	1	2	14	0
	Flex	.09	.00	.00	1.09	.39	.41	.73	.21	1.28	.80	.50	1.72	1.42	0.00
	Rigid	.19	.00	.00	1.54	.39	.74	1.59	.26	2.46	2.01	.48	3.56	2.16	0.00
	GVW	5.8	2.6	4.6	38.1	18.8	30.5	61.0	24.1	63.9	79.9	37.4	82.3	68.9	0.0
S Lane1	Num	2	1,910	1,152	3	49	54	2	36	174	38	0	1	12	0
	Flex	.13	.00	.00	.87	.68	.67	1.69	.50	1.59	1.25	0.00	.87	1.43	0.00
	Rigid	.28	.00	.00	1.18	.69	1.23	4.19	.63	3.07	3.04	0.00	1.35	2.57	0.00
	GVW	7.5	3.1	5.4	34.6	22.3	36.6	76.9	29.7	67.7	83.4	0.0	57.2	81.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2022

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9