

Idaho Transportation Department

Monthly WIM Distribution for Oct-2022

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	3,890	2,210	7	100	135	7	76	376	72	1	3	35	0
	Flex	.30	.00	.00	.62	.51	.51	1.26	.34	1.39	.88	.81	2.88	1.71	0.00
	Rigid	.65	.00	.00	.89	.52	.92	3.01	.41	2.64	2.25	.81	5.27	2.72	0.00
	GVW	12.7	2.8	4.9	31.9	20.6	32.6	76.0	26.5	65.3	80.0	41.2	90.7	78.3	0.0
N	Num	2	1,917	1,097	4	50	66	5	40	200	37	1	2	18	0
	Flex	.17	.00	.00	.68	.46	.38	1.16	.19	1.25	.71	.07	3.07	1.73	0.00
	Rigid	.37	.00	.00	.95	.47	.69	2.68	.21	2.38	1.79	.06	5.66	2.66	0.00
	GVW	10.0	2.6	4.7	35.4	19.6	29.1	72.7	23.2	63.8	76.4	28.6	93.8	76.4	0.0
S	Num	2	1,973	1,112	3	50	70	2	35	176	35	1	1	17	0
	Flex	.23	.00	.00	.68	.57	.63	1.68	.51	1.53	1.07	1.06	.99	1.67	0.00
	Rigid	.50	.00	.00	.97	.57	1.15	4.25	.64	2.91	2.76	1.06	1.66	2.77	0.00
	GVW	8.9	3.1	5.2	26.6	21.6	36.4	87.5	30.3	66.8	83.7	45.4	72.4	79.9	0.0
N Lane1	Num	2	1,917	1,097	4	50	66	5	40	200	37	1	2	18	0
	Flex	.17	.00	.00	.68	.46	.38	1.16	.19	1.25	.71	.07	3.07	1.73	0.00
	Rigid	.37	.00	.00	.95	.47	.69	2.68	.21	2.38	1.79	.06	5.66	2.66	0.00
	GVW	10.0	2.6	4.7	35.4	19.6	29.1	72.7	23.2	63.8	76.4	28.6	93.8	76.4	0.0
S Lane1	Num	2	1,973	1,112	3	50	70	2	35	176	35	1	1	17	0
	Flex	.23	.00	.00	.68	.57	.63	1.68	.51	1.53	1.07	1.06	.99	1.67	0.00
	Rigid	.50	.00	.00	.97	.57	1.15	4.25	.64	2.91	2.76	1.06	1.66	2.77	0.00
	GVW	8.9	3.1	5.2	26.6	21.6	36.4	87.5	30.3	66.8	83.7	45.4	72.4	79.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2022

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9