

Idaho Transportation Department

Monthly WIM Distribution for Nov-2022

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	3,450	1,920	6	80	75	5	64	297	49	1	4	25	0
	Flex	.17	.00	.00	.62	.36	.55	.68	.26	1.15	.72	3.07	1.47	.98	0.00
	Rigid	.38	.00	.00	.84	.35	.98	1.81	.31	2.15	1.83	3.07	2.78	1.56	0.00
	GVW	11.5	2.8	4.8	30.2	18.9	34.5	61.4	26.8	63.5	79.2	71.8	69.8	71.2	0.0
N	Num	3	1,701	947	4	41	37	4	34	157	26	1	3	13	0
	Flex	.31	.00	.00	.47	.24	.37	.56	.14	1.01	.64	2.96	1.98	1.05	0.00
	Rigid	.66	.00	.00	.66	.24	.63	1.47	.16	1.88	1.62	2.96	3.77	1.57	0.00
	GVW	17.3	2.6	4.5	28.4	17.2	30.0	58.4	23.8	62.2	78.7	69.2	82.4	72.4	0.0
S	Num	2	1,748	973	2	38	39	2	30	139	23	1	2	12	0
	Flex	.04	.00	.00	.74	.47	.71	1.04	.38	1.30	.82	1.51	.83	.87	0.00
	Rigid	.10	.00	.00	1.01	.47	1.29	2.85	.46	2.42	2.07	1.43	1.54	1.50	0.00
	GVW	7.8	3.0	5.0	29.8	20.7	38.3	71.1	30.2	64.8	79.5	61.7	57.7	68.9	0.0
N Lane1	Num	3	1,701	947	4	41	37	4	34	157	26	1	3	13	0
	Flex	.31	.00	.00	.47	.24	.37	.56	.14	1.01	.64	2.96	1.98	1.05	0.00
	Rigid	.66	.00	.00	.66	.24	.63	1.47	.16	1.88	1.62	2.96	3.77	1.57	0.00
	GVW	17.3	2.6	4.5	28.4	17.2	30.0	58.4	23.8	62.2	78.7	69.2	82.4	72.4	0.0
S Lane1	Num	2	1,748	973	2	38	39	2	30	139	23	1	2	12	0
	Flex	.04	.00	.00	.74	.47	.71	1.04	.38	1.30	.82	1.51	.83	.87	0.00
	Rigid	.10	.00	.00	1.01	.47	1.29	2.85	.46	2.42	2.07	1.43	1.54	1.50	0.00
	GVW	7.8	3.0	5.0	29.8	20.7	38.3	71.1	30.2	64.8	79.5	61.7	57.7	68.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2022

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9