

Idaho Transportation Department

Monthly WIM Distribution for Dec-2022

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	3,287	1,664	5	63	58	5	45	274	47	1	4	77	0
	Flex	.73	.00	.00	.58	.48	.62	1.13	.35	1.32	.90	1.89	2.91	1.05	0.00
	Rigid	1.74	.00	.00	.81	.48	1.11	2.98	.43	2.53	2.30	1.87	5.57	1.89	0.00
	GVW	18.6	3.2	5.0	31.9	19.6	34.9	72.9	28.5	65.7	82.2	58.2	84.3	76.1	0.0
N	Num	2	1,619	833	4	33	28	4	24	153	24	1	3	38	0
	Flex	.91	.00	.00	.57	.33	.41	1.05	.18	1.18	.76	1.36	3.92	.76	0.00
	Rigid	2.07	.00	.00	.80	.32	.70	2.70	.21	2.27	1.94	1.34	7.69	1.20	0.00
	GVW	20.5	3.0	4.7	32.6	18.2	32.2	68.3	25.5	65.0	81.8	53.1	96.4	68.5	0.0
S	Num	1	1,669	831	2	30	30	2	21	121	23	1	2	39	0
	Flex	.16	.00	.00	.64	.68	.83	1.74	.54	1.52	1.01	1.75	1.14	1.33	0.00
	Rigid	.58	.00	.00	.87	.70	1.51	4.73	.69	2.93	2.61	1.73	1.44	2.56	0.00
	GVW	13.4	3.3	5.2	30.9	21.3	37.3	89.0	32.1	67.2	81.5	47.8	55.5	83.8	0.0
N Lane1	Num	2	1,619	833	4	33	28	4	24	153	24	1	3	38	0
	Flex	.91	.00	.00	.57	.33	.41	1.05	.18	1.18	.76	1.36	3.92	.76	0.00
	Rigid	2.07	.00	.00	.80	.32	.70	2.70	.21	2.27	1.94	1.34	7.69	1.20	0.00
	GVW	20.5	3.0	4.7	32.6	18.2	32.2	68.3	25.5	65.0	81.8	53.1	96.4	68.5	0.0
S Lane1	Num	1	1,669	831	2	30	30	2	21	121	23	1	2	39	0
	Flex	.16	.00	.00	.64	.68	.83	1.74	.54	1.52	1.01	1.75	1.14	1.33	0.00
	Rigid	.58	.00	.00	.87	.70	1.51	4.73	.69	2.93	2.61	1.73	1.44	2.56	0.00
	GVW	13.4	3.3	5.2	30.9	21.3	37.3	89.0	32.1	67.2	81.5	47.8	55.5	83.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2022

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9