

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2023

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	3,198	1,705	6	68	52	7	52	273	42	0	3	19	0
	Flex	.04	.00	.00	.72	.35	.64	1.80	.33	1.27	.81	0.00	3.83	1.09	0.00
	Rigid	.08	.00	.00	1.00	.35	1.13	4.73	.41	2.37	2.07	0.00	7.63	1.83	0.00
	GVW	5.0	3.0	5.0	31.5	18.6	35.1	80.5	29.0	65.0	81.1	0.0	98.4	76.7	0.0
N	Num	1	1,567	848	4	37	24	7	27	149	20	0	2	10	0
	Flex	.02	.00	.00	.68	.21	.44	1.93	.16	1.06	.66	0.00	4.09	1.13	0.00
	Rigid	.03	.01	.00	.95	.20	.75	5.11	.19	1.98	1.71	0.00	8.46	1.73	0.00
	GVW	5.8	3.0	4.7	32.8	16.3	31.8	83.1	25.0	63.3	78.6	0.0	105.2	77.7	0.0
S	Num	1	1,631	858	2	31	29	1	25	125	22	0	2	10	0
	Flex	.08	.00	.00	.79	.53	.82	.80	.51	1.51	.96	0.00	1.79	1.05	0.00
	Rigid	.17	.00	.00	1.07	.53	1.46	1.94	.64	2.82	2.42	0.00	2.51	1.96	0.00
	GVW	5.5	3.0	5.2	30.3	21.4	38.3	64.0	33.4	67.1	83.6	0.0	69.8	76.2	0.0
N Lane1	Num	1	1,567	848	4	37	24	7	27	149	20	0	2	10	0
	Flex	.02	.00	.00	.68	.21	.44	1.93	.16	1.06	.66	0.00	4.09	1.13	0.00
	Rigid	.03	.01	.00	.95	.20	.75	5.11	.19	1.98	1.71	0.00	8.46	1.73	0.00
	GVW	5.8	3.0	4.7	32.8	16.3	31.8	83.1	25.0	63.3	78.6	0.0	105.2	77.7	0.0
S Lane1	Num	1	1,631	858	2	31	29	1	25	125	22	0	2	10	0
	Flex	.08	.00	.00	.79	.53	.82	.80	.51	1.51	.96	0.00	1.79	1.05	0.00
	Rigid	.17	.00	.00	1.07	.53	1.46	1.94	.64	2.82	2.42	0.00	2.51	1.96	0.00
	GVW	5.5	3.0	5.2	30.3	21.4	38.3	64.0	33.4	67.1	83.6	0.0	69.8	76.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2023

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9