

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2023

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	3,759	1,928	6	80	54	7	68	299	58	1	3	25	0
	Flex	.58	.00	.01	.93	.48	.69	1.93	.39	1.53	.93	.36	2.99	1.64	0.00
	Rigid	1.36	.00	.01	1.55	.48	1.27	5.14	.49	2.88	2.35	.34	6.22	3.08	0.00
	GVW	13.8	3.4	5.6	35.7	20.6	36.2	76.2	29.7	68.1	83.5	36.7	84.0	94.2	0.0
N	Num	2	1,826	991	4	42	26	5	36	155	32	1	2	13	0
	Flex	.69	.00	.01	.87	.26	.54	2.18	.20	1.26	.68	.37	3.80	1.27	0.00
	Rigid	1.63	.00	.01	1.20	.26	.96	5.83	.24	2.40	1.74	.36	8.11	1.96	0.00
	GVW	14.5	3.2	5.1	37.6	17.3	33.2	80.3	25.5	65.1	78.6	37.6	94.1	78.4	0.0
S	Num	2	1,933	938	2	39	29	2	32	144	26	1	2	12	0
	Flex	.20	.00	.00	.90	.72	.82	.62	.60	1.80	1.17	.01	1.28	1.95	0.00
	Rigid	.43	.00	.00	1.63	.73	1.52	1.59	.77	3.37	2.96	.02	1.55	4.16	0.00
	GVW	10.9	3.7	6.2	33.5	24.3	38.1	56.0	34.3	71.1	88.5	24.3	61.0	110.3	0.0
N Lane1	Num	2	1,826	991	4	42	26	5	36	155	32	1	2	13	0
	Flex	.69	.00	.01	.87	.26	.54	2.18	.20	1.26	.68	.37	3.80	1.27	0.00
	Rigid	1.63	.00	.01	1.20	.26	.96	5.83	.24	2.40	1.74	.36	8.11	1.96	0.00
	GVW	14.5	3.2	5.1	37.6	17.3	33.2	80.3	25.5	65.1	78.6	37.6	94.1	78.4	0.0
S Lane1	Num	2	1,933	938	2	39	29	2	32	144	26	1	2	12	0
	Flex	.20	.00	.00	.90	.72	.82	.62	.60	1.80	1.17	.01	1.28	1.95	0.00
	Rigid	.43	.00	.00	1.63	.73	1.52	1.59	.77	3.37	2.96	.02	1.55	4.16	0.00
	GVW	10.9	3.7	6.2	33.5	24.3	38.1	56.0	34.3	71.1	88.5	24.3	61.0	110.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2023

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9