

Idaho Transportation Department

Monthly WIM Distribution for Jan-2015

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	1	1	0	0	0	0	1	1	1	0	0	0	0
	Flex	.00	.00	.00	0.00	0.00	0.00	0.00	.01	.23	.01	0.00	0.00	0.00	0.00
	Rigid	.00	.00	.00	0.00	0.00	0.00	0.00	.01	.27	.03	0.00	0.00	0.00	0.00
	GVW	1.7	3.1	2.5	0.0	0.0	0.0	0.0	12.1	27.1	33.6	0.0	0.0	0.0	0.0
E	Num	1	1	1	0	0	0	0	1	1	1	0	0	0	0
	Flex	.00	.00	.00	0.00	0.00	0.00	0.00	.01	.23	.01	0.00	0.00	0.00	0.00
	Rigid	.00	.00	.00	0.00	0.00	0.00	0.00	.01	.27	.03	0.00	0.00	0.00	0.00
	GVW	1.7	3.1	2.5	0.0	0.0	0.0	0.0	12.1	27.1	33.6	0.0	0.0	0.0	0.0
W	Num	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
E Lane1	Num	1	1	1	0	0	0	0	1	1	1	0	0	0	0
	Flex	.00	.00	.00	0.00	0.00	0.00	0.00	.01	.23	.01	0.00	0.00	0.00	0.00
	Rigid	.00	.00	.00	0.00	0.00	0.00	0.00	.01	.27	.03	0.00	0.00	0.00	0.00
	GVW	1.7	3.1	2.5	0.0	0.0	0.0	0.0	12.1	27.1	33.6	0.0	0.0	0.0	0.0
W Lane1	Num	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Flex	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	Rigid	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	GVW	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2015

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9