

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2015

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	375	355	2	8	6	2	16	193	38	5	3	43	0
	Flex	.00	.00	.00	2.48	1.90	1.43	1.36	.96	2.52	1.01	1.94	2.06	1.37	0.00
	Rigid	.00	.00	.00	3.78	2.33	2.30	1.62	1.13	4.76	2.07	2.19	2.91	2.17	0.00
	GVW	2.2	2.8	3.4	40.2	24.0	27.1	25.0	23.5	59.2	52.4	40.8	53.7	59.5	0.0
E	Num	1	186	180	1	4	4	1	8	99	24	3	2	24	0
	Flex	.00	.00	.00	1.76	1.54	1.08	2.15	.80	1.92	.47	2.26	1.51	.92	0.00
	Rigid	.00	.00	.00	3.44	1.79	1.51	2.45	.91	3.29	.97	2.59	1.97	1.30	0.00
	GVW	2.7	2.8	3.2	36.1	22.9	24.7	32.3	24.2	50.7	41.7	44.5	46.6	51.9	0.0
W	Num	2	189	176	1	4	3	2	7	94	13	3	3	19	0
	Flex	.00	.00	.00	3.52	2.33	1.70	.97	.99	3.22	2.07	1.84	2.10	1.85	0.00
	Rigid	.00	.00	.00	5.21	2.90	2.98	1.23	1.19	6.43	4.43	2.08	3.44	3.15	0.00
	GVW	1.7	2.8	3.7	42.5	24.7	28.8	23.9	21.6	68.1	75.1	38.2	59.6	67.4	0.0
E Lane1	Num	1	186	180	1	4	4	1	8	99	24	3	2	24	0
	Flex	.00	.00	.00	1.76	1.54	1.08	2.15	.80	1.92	.47	2.26	1.51	.92	0.00
	Rigid	.00	.00	.00	3.44	1.79	1.51	2.45	.91	3.29	.97	2.59	1.97	1.30	0.00
	GVW	2.7	2.8	3.2	36.1	22.9	24.7	32.3	24.2	50.7	41.7	44.5	46.6	51.9	0.0
W Lane1	Num	2	189	176	1	4	3	2	7	94	13	3	3	19	0
	Flex	.00	.00	.00	3.52	2.33	1.70	.97	.99	3.22	2.07	1.84	2.10	1.85	0.00
	Rigid	.00	.00	.00	5.21	2.90	2.98	1.23	1.19	6.43	4.43	2.08	3.44	3.15	0.00
	GVW	1.7	2.8	3.7	42.5	24.7	28.8	23.9	21.6	68.1	75.1	38.2	59.6	67.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2015

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9