

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2017

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	258	317	5	28	8	1	10	287	6	13	5	9	0
	Flex	.00	.00	.00	.31	.15	.54	.95	.32	.58	.46	.60	.33	.57	0.00
	Rigid	.00	.00	.00	.32	.15	.73	1.09	.35	.96	.88	.57	.33	.81	0.00
	GVW	3.9	3.4	6.2	22.4	17.3	30.2	41.8	30.2	54.1	62.2	46.5	46.6	61.7	0.0
E	Num	2	132	156	2	12	4	1	5	148	3	7	3	6	0
	Flex	.00	.00	.00	.30	.11	.49	2.09	.32	.47	.37	.66	.44	.57	0.00
	Rigid	.00	.00	.00	.30	.10	.66	2.34	.35	.76	.65	.62	.44	.77	0.00
	GVW	4.0	3.3	6.2	22.4	17.1	28.9	50.1	30.2	50.4	57.2	49.8	53.4	59.4	0.0
W	Num	2	131	167	3	16	4	1	5	143	3	6	2	3	0
	Flex	.00	.00	.00	.32	.17	.72	.57	.34	.70	.55	.52	.18	.60	0.00
	Rigid	.00	.00	.00	.34	.18	.96	.67	.37	1.18	1.08	.50	.18	.96	0.00
	GVW	3.8	3.4	6.3	22.8	17.3	33.2	39.0	29.8	58.1	65.1	42.2	39.1	69.7	0.0
E Lane1	Num	2	132	156	2	12	4	1	5	148	3	7	3	6	0
	Flex	.00	.00	.00	.30	.11	.49	2.09	.32	.47	.37	.66	.44	.57	0.00
	Rigid	.00	.00	.00	.30	.10	.66	2.34	.35	.76	.65	.62	.44	.77	0.00
	GVW	4.0	3.3	6.2	22.4	17.1	28.9	50.1	30.2	50.4	57.2	49.8	53.4	59.4	0.0
W Lane1	Num	2	131	167	3	16	4	1	5	143	3	6	2	3	0
	Flex	.00	.00	.00	.32	.17	.72	.57	.34	.70	.55	.52	.18	.60	0.00
	Rigid	.00	.00	.00	.34	.18	.96	.67	.37	1.18	1.08	.50	.18	.96	0.00
	GVW	3.8	3.4	6.3	22.8	17.3	33.2	39.0	29.8	58.1	65.1	42.2	39.1	69.7	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2017

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9