

# Idaho Transportation Department

## Monthly WIM Distribution for May-2017

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	758	665	13	132	29	2	14	316	6	4	5	16	0
	Flex	.00	.00	.00	.93	.16	.89	1.31	.33	1.47	1.01	2.24	.46	1.10	0.00
	Rigid	.00	.00	.00	1.22	.17	1.52	3.41	.37	2.72	1.94	2.49	.49	1.76	0.00
	GVW	3.2	3.6	6.2	27.4	17.7	33.4	67.0	26.3	57.2	64.9	48.9	43.8	60.9	0.0
E	Num	5	411	340	6	73	9	1	8	161	3	2	3	9	0
	Flex	.00	.00	.00	.94	.17	.61	.26	.31	1.38	1.01	3.27	.67	1.45	0.00
	Rigid	.00	.00	.00	1.14	.18	.94	1.01	.35	2.50	1.87	3.65	.73	2.16	0.00
	GVW	3.6	3.7	6.5	25.6	18.0	28.7	55.7	26.7	58.3	64.4	60.4	50.8	68.0	0.0
W	Num	7	348	325	6	58	20	2	6	155	3	2	2	6	0
	Flex	.00	.00	.00	.82	.17	.99	1.31	.33	1.55	.73	.23	.23	.84	0.00
	Rigid	.00	.00	.00	1.16	.18	1.71	3.41	.37	2.96	1.41	.22	.23	1.77	0.00
	GVW	3.2	3.5	5.8	27.8	17.3	35.4	67.0	26.5	55.7	60.6	32.9	36.9	53.7	0.0
E Lane1	Num	5	411	340	6	73	9	1	8	161	3	2	3	9	0
	Flex	.00	.00	.00	.94	.17	.61	.26	.31	1.38	1.01	3.27	.67	1.45	0.00
	Rigid	.00	.00	.00	1.14	.18	.94	1.01	.35	2.50	1.87	3.65	.73	2.16	0.00
	GVW	3.6	3.7	6.5	25.6	18.0	28.7	55.7	26.7	58.3	64.4	60.4	50.8	68.0	0.0
W Lane1	Num	7	348	325	6	58	20	2	6	155	3	2	2	6	0
	Flex	.00	.00	.00	.82	.17	.99	1.31	.33	1.55	.73	.23	.23	.84	0.00
	Rigid	.00	.00	.00	1.16	.18	1.71	3.41	.37	2.96	1.41	.22	.23	1.77	0.00
	GVW	3.2	3.5	5.8	27.8	17.3	35.4	67.0	26.5	55.7	60.6	32.9	36.9	53.7	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for May-2017

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9