

Idaho Transportation Department

Monthly WIM Distribution for Sep-2017

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	16	692	605	17	162	51	4	12	316	10	4	5	18	0
	Flex	.00	.00	.00	1.15	.21	1.38	1.26	.54	1.77	1.11	1.45	.48	.92	0.00
	Rigid	.00	.00	.00	1.49	.23	2.54	2.29	.67	3.38	2.10	1.59	.51	1.28	0.00
	GVW	3.8	3.7	6.1	28.1	17.9	36.8	53.8	27.0	59.0	65.6	45.2	46.6	60.9	0.0
E	Num	8	373	319	8	73	16	3	6	170	6	3	3	10	0
	Flex	.00	.00	.00	.72	.16	.53	1.32	.48	1.42	1.39	1.36	.34	1.17	0.00
	Rigid	.00	.00	.00	.82	.17	.78	2.05	.55	2.55	2.56	1.48	.35	1.47	0.00
	GVW	3.9	3.7	6.5	25.1	17.6	27.9	50.9	25.9	58.3	77.6	48.2	45.7	66.9	0.0
W	Num	9	319	285	9	89	36	2	6	146	5	2	3	8	0
	Flex	.00	.00	.00	1.51	.25	1.84	.85	.64	2.09	.65	3.32	.61	.57	0.00
	Rigid	.00	.00	.00	2.06	.26	3.45	1.86	.81	4.19	1.35	3.87	.67	1.03	0.00
	GVW	3.7	3.8	5.8	30.4	17.9	41.7	50.5	29.0	58.9	53.8	42.7	44.0	51.5	0.0
E Lane1	Num	8	373	319	8	73	16	3	6	170	6	3	3	10	0
	Flex	.00	.00	.00	.72	.16	.53	1.32	.48	1.42	1.39	1.36	.34	1.17	0.00
	Rigid	.00	.00	.00	.82	.17	.78	2.05	.55	2.55	2.56	1.48	.35	1.47	0.00
	GVW	3.9	3.7	6.5	25.1	17.6	27.9	50.9	25.9	58.3	77.6	48.2	45.7	66.9	0.0
W Lane1	Num	9	319	285	9	89	36	2	6	146	5	2	3	8	0
	Flex	.00	.00	.00	1.51	.25	1.84	.85	.64	2.09	.65	3.32	.61	.57	0.00
	Rigid	.00	.00	.00	2.06	.26	3.45	1.86	.81	4.19	1.35	3.87	.67	1.03	0.00
	GVW	3.7	3.8	5.8	30.4	17.9	41.7	50.5	29.0	58.9	53.8	42.7	44.0	51.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2017

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9