

Idaho Transportation Department

Monthly WIM Distribution for Nov-2017

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	606	580	7	92	7	1	10	340	11	6	7	23	0
	Flex	.00	.00	.00	.43	.12	.48	.73	.41	1.09	.51	1.14	1.01	.97	0.00
	Rigid	.00	.00	.00	.48	.12	.65	1.21	.43	1.95	.99	1.10	1.07	1.23	0.00
	GVW	4.3	3.6	6.8	23.5	17.2	26.5	49.6	29.2	62.5	61.1	55.5	57.9	67.9	0.0
E	Num	1	295	308	4	26	4	1	5	161	5	4	3	13	0
	Flex	.00	.00	.00	.28	.06	.25	1.67	.18	.53	.32	1.00	.42	.74	0.00
	Rigid	.00	.00	.00	.28	.06	.28	1.93	.18	.85	.55	.95	.42	.88	0.00
	GVW	5.6	3.4	6.5	20.5	17.2	23.5	52.5	26.9	53.0	52.6	55.1	50.8	64.9	0.0
W	Num	2	311	272	4	66	4	1	5	179	6	3	3	10	0
	Flex	.00	.00	.00	.58	.14	.92	.59	.57	1.61	.68	1.17	1.32	1.34	0.00
	Rigid	.00	.00	.00	.68	.15	1.32	1.09	.61	2.95	1.35	1.14	1.40	1.85	0.00
	GVW	1.6	3.8	7.1	26.3	17.2	32.1	49.6	31.1	71.0	69.1	53.6	58.9	74.4	0.0
E Lane1	Num	1	295	308	4	26	4	1	5	161	5	4	3	13	0
	Flex	.00	.00	.00	.28	.06	.25	1.67	.18	.53	.32	1.00	.42	.74	0.00
	Rigid	.00	.00	.00	.28	.06	.28	1.93	.18	.85	.55	.95	.42	.88	0.00
	GVW	5.6	3.4	6.5	20.5	17.2	23.5	52.5	26.9	53.0	52.6	55.1	50.8	64.9	0.0
W Lane1	Num	2	311	272	4	66	4	1	5	179	6	3	3	10	0
	Flex	.00	.00	.00	.58	.14	.92	.59	.57	1.61	.68	1.17	1.32	1.34	0.00
	Rigid	.00	.00	.00	.68	.15	1.32	1.09	.61	2.95	1.35	1.14	1.40	1.85	0.00
	GVW	1.6	3.8	7.1	26.3	17.2	32.1	49.6	31.1	71.0	69.1	53.6	58.9	74.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2017

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9