

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2018

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	793	615	11	169	8	1	12	382	11	9	7	24	0
	Flex	.00	.00	.00	.68	.20	.97	1.02	.63	2.64	1.20	2.52	2.88	1.95	0.00
	Rigid	.00	.00	.00	.77	.21	1.59	2.10	.71	5.05	2.39	2.69	3.44	2.93	0.00
	GVW	3.6	3.9	6.8	25.0	17.0	32.0	59.0	30.2	72.4	70.3	61.0	68.9	80.6	0.0
E	Num	1	387	364	6	29	5	1	5	185	6	4	4	13	0
	Flex	.00	.00	.00	.28	.06	.18	1.22	.22	.48	.31	1.02	.46	.61	0.00
	Rigid	.00	.00	.00	.28	.06	.22	1.41	.22	.78	.60	.99	.46	.76	0.00
	GVW	3.4	3.4	6.3	21.4	16.7	22.6	49.2	27.3	51.4	60.1	54.5	54.5	64.0	0.0
W	Num	1	406	251	6	140	4	1	8	197	6	5	4	12	0
	Flex	.00	.00	.00	1.11	.23	1.87	1.00	.91	4.64	1.92	3.63	4.80	4.02	0.00
	Rigid	.00	.00	.00	1.26	.25	3.11	2.33	1.04	9.01	3.83	3.94	5.73	5.98	0.00
	GVW	3.2	4.5	7.4	29.0	17.1	41.6	62.1	32.5	91.8	77.3	65.2	81.8	103.9	0.0
E Lane1	Num	1	387	364	6	29	5	1	5	185	6	4	4	13	0
	Flex	.00	.00	.00	.28	.06	.18	1.22	.22	.48	.31	1.02	.46	.61	0.00
	Rigid	.00	.00	.00	.28	.06	.22	1.41	.22	.78	.60	.99	.46	.76	0.00
	GVW	3.4	3.4	6.3	21.4	16.7	22.6	49.2	27.3	51.4	60.1	54.5	54.5	64.0	0.0
W Lane1	Num	1	406	251	6	140	4	1	8	197	6	5	4	12	0
	Flex	.00	.00	.00	1.11	.23	1.87	1.00	.91	4.64	1.92	3.63	4.80	4.02	0.00
	Rigid	.00	.00	.00	1.26	.25	3.11	2.33	1.04	9.01	3.83	3.94	5.73	5.98	0.00
	GVW	3.2	4.5	7.4	29.0	17.1	41.6	62.1	32.5	91.8	77.3	65.2	81.8	103.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2018

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9