

Idaho Transportation Department

Monthly WIM Distribution for Dec-2018

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	527	521	9	52	7	2	11	344	7	14	7	15	0
	Flex	.00	.00	.00	.37	.11	.43	1.56	.33	.84	.51	1.11	.62	.66	0.00
	Rigid	.00	.00	.00	.44	.11	.58	2.33	.35	1.50	1.01	1.14	.65	.96	0.00
	GVW	3.4	3.5	6.2	21.9	16.8	26.0	52.9	28.7	56.2	59.1	50.9	51.4	61.7	0.0
E	Num	1	262	268	4	16	5	2	6	163	4	6	3	9	0
	Flex	.00	.00	.00	.20	.07	.19	1.33	.17	.39	.27	.76	.31	.41	0.00
	Rigid	.00	.00	.00	.20	.07	.22	1.48	.18	.61	.47	.72	.31	.54	0.00
	GVW	3.3	3.3	6.0	20.3	16.7	22.2	47.2	27.0	48.8	51.2	52.9	49.2	55.4	0.0
W	Num	2	265	253	5	37	3	1	5	181	4	8	4	7	0
	Flex	.00	.00	.00	.51	.13	.87	2.31	.46	1.23	.66	1.27	.91	1.03	0.00
	Rigid	.00	.00	.00	.63	.13	1.27	3.53	.49	2.26	1.35	1.32	.99	1.55	0.00
	GVW	3.0	3.7	6.5	23.3	16.9	32.8	57.9	30.3	62.6	64.2	48.9	52.0	72.4	0.0
E Lane1	Num	1	262	268	4	16	5	2	6	163	4	6	3	9	0
	Flex	.00	.00	.00	.20	.07	.19	1.33	.17	.39	.27	.76	.31	.41	0.00
	Rigid	.00	.00	.00	.20	.07	.22	1.48	.18	.61	.47	.72	.31	.54	0.00
	GVW	3.3	3.3	6.0	20.3	16.7	22.2	47.2	27.0	48.8	51.2	52.9	49.2	55.4	0.0
W Lane1	Num	2	265	253	5	37	3	1	5	181	4	8	4	7	0
	Flex	.00	.00	.00	.51	.13	.87	2.31	.46	1.23	.66	1.27	.91	1.03	0.00
	Rigid	.00	.00	.00	.63	.13	1.27	3.53	.49	2.26	1.35	1.32	.99	1.55	0.00
	GVW	3.0	3.7	6.5	23.3	16.9	32.8	57.9	30.3	62.6	64.2	48.9	52.0	72.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2018

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9