

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	459	473	9	52	6	1	10	372	11	11	6	19	0
	Flex	.00	.00	.00	.36	.10	.49	.40	.39	.94	.43	1.11	1.03	.83	0.00
	Rigid	.00	.00	.00	.40	.11	.66	1.40	.42	1.64	.77	1.10	1.12	1.14	0.00
	GVW	3.2	3.5	6.3	23.2	16.6	25.7	57.9	29.1	57.7	53.4	52.6	57.4	64.3	0.0
E	Num	1	230	241	5	17	3	0	5	179	6	6	4	11	0
	Flex	.00	.00	.00	.32	.08	.22	0.00	.23	.45	.26	1.16	.48	.54	0.00
	Rigid	.00	.00	.00	.32	.08	.24	0.00	.23	.71	.43	1.13	.49	.69	0.00
	GVW	5.0	3.4	6.1	22.1	16.9	22.3	0.0	27.7	49.0	48.6	56.7	54.6	57.7	0.0
W	Num	1	229	232	5	35	3	1	5	193	5	6	3	8	0
	Flex	.00	.00	.00	.37	.12	.98	.40	.50	1.36	.68	1.08	1.37	1.30	0.00
	Rigid	.00	.00	.00	.42	.12	1.40	1.40	.55	2.43	1.32	1.09	1.51	1.87	0.00
	GVW	2.4	3.7	6.6	23.5	16.6	31.5	57.9	29.8	65.3	63.8	48.3	57.9	76.3	0.0
E Lane1	Num	1	230	241	5	17	3	0	5	179	6	6	4	11	0
	Flex	.00	.00	.00	.32	.08	.22	0.00	.23	.45	.26	1.16	.48	.54	0.00
	Rigid	.00	.00	.00	.32	.08	.24	0.00	.23	.71	.43	1.13	.49	.69	0.00
	GVW	5.0	3.4	6.1	22.1	16.9	22.3	0.0	27.7	49.0	48.6	56.7	54.6	57.7	0.0
W Lane1	Num	1	229	232	5	35	3	1	5	193	5	6	3	8	0
	Flex	.00	.00	.00	.37	.12	.98	.40	.50	1.36	.68	1.08	1.37	1.30	0.00
	Rigid	.00	.00	.00	.42	.12	1.40	1.40	.55	2.43	1.32	1.09	1.51	1.87	0.00
	GVW	2.4	3.7	6.6	23.5	16.6	31.5	57.9	29.8	65.3	63.8	48.3	57.9	76.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9