

Idaho Transportation Department

Monthly WIM Distribution for Apr-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	6	722	642	14	132	14	2	11	380	13	8	6	20	0
	Flex	.00	.00	.00	.75	.12	.61	.90	.34	1.63	.66	.99	.45	.83	0.00
	Rigid	.00	.00	.00	1.00	.13	.93	2.45	.38	3.06	1.35	.98	.46	1.22	0.00
	GVW	3.1	3.7	6.5	25.1	17.3	27.8	53.8	28.4	61.9	60.2	50.1	48.2	65.3	0.0
E	Num	3	376	346	8	54	6	2	6	184	7	5	3	11	0
	Flex	.00	.00	.00	.40	.10	.30	1.98	.31	.72	.57	.95	.42	.76	0.00
	Rigid	.00	.00	.00	.44	.10	.38	4.56	.35	1.20	1.13	.91	.43	1.02	0.00
	GVW	2.9	3.5	6.5	23.1	17.5	22.6	57.5	27.9	53.3	57.0	53.2	52.5	63.2	0.0
W	Num	3	346	296	6	78	8	1	6	196	6	5	3	9	0
	Flex	.00	.00	.00	1.00	.13	.89	.39	.39	2.48	.74	.91	.47	.85	0.00
	Rigid	.00	.00	.00	1.42	.14	1.42	1.48	.43	4.82	1.59	.93	.50	1.42	0.00
	GVW	3.1	3.8	6.6	26.0	17.1	32.3	49.5	29.0	69.8	63.2	42.2	43.2	67.1	0.0
E Lane1	Num	3	376	346	8	54	6	2	6	184	7	5	3	11	0
	Flex	.00	.00	.00	.40	.10	.30	1.98	.31	.72	.57	.95	.42	.76	0.00
	Rigid	.00	.00	.00	.44	.10	.38	4.56	.35	1.20	1.13	.91	.43	1.02	0.00
	GVW	2.9	3.5	6.5	23.1	17.5	22.6	57.5	27.9	53.3	57.0	53.2	52.5	63.2	0.0
W Lane1	Num	3	346	296	6	78	8	1	6	196	6	5	3	9	0
	Flex	.00	.00	.00	1.00	.13	.89	.39	.39	2.48	.74	.91	.47	.85	0.00
	Rigid	.00	.00	.00	1.42	.14	1.42	1.48	.43	4.82	1.59	.93	.50	1.42	0.00
	GVW	3.1	3.8	6.6	26.0	17.1	32.3	49.5	29.0	69.8	63.2	42.2	43.2	67.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9