

Idaho Transportation Department

Monthly WIM Distribution for May-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	13	843	698	17	163	24	3	11	361	14	7	5	18	0
	Flex	.00	.00	.00	.80	.14	.90	1.33	.58	1.88	.78	.93	.54	.84	0.00
	Rigid	.00	.00	.00	1.05	.15	1.57	3.38	.70	3.55	1.56	.91	.57	1.27	0.00
	GVW	3.7	3.7	6.4	25.2	17.3	32.0	61.0	28.2	61.7	59.9	49.6	48.6	61.8	0.0
E	Num	7	432	367	9	71	8	6	5	178	9	4	3	11	0
	Flex	.00	.00	.00	.60	.12	.40	1.72	.54	1.14	.84	1.31	.48	.95	0.00
	Rigid	.00	.00	.00	.68	.13	.59	3.64	.67	2.04	1.75	1.30	.50	1.41	0.00
	GVW	4.0	3.6	6.5	23.1	17.6	25.5	67.6	26.8	57.5	63.1	56.4	48.7	66.1	0.0
W	Num	6	411	330	8	92	17	2	6	183	6	3	3	7	0
	Flex	.00	.00	.00	.96	.16	1.27	1.28	.54	2.53	.79	.35	.54	.58	0.00
	Rigid	.00	.00	.00	1.34	.17	2.29	3.63	.62	4.90	1.54	.33	.57	.92	0.00
	GVW	3.5	3.8	6.2	26.9	17.1	37.1	62.1	28.7	65.3	56.1	37.0	45.7	53.1	0.0
E Lane1	Num	7	432	367	9	71	8	6	5	178	9	4	3	11	0
	Flex	.00	.00	.00	.60	.12	.40	1.72	.54	1.14	.84	1.31	.48	.95	0.00
	Rigid	.00	.00	.00	.68	.13	.59	3.64	.67	2.04	1.75	1.30	.50	1.41	0.00
	GVW	4.0	3.6	6.5	23.1	17.6	25.5	67.6	26.8	57.5	63.1	56.4	48.7	66.1	0.0
W Lane1	Num	6	411	330	8	92	17	2	6	183	6	3	3	7	0
	Flex	.00	.00	.00	.96	.16	1.27	1.28	.54	2.53	.79	.35	.54	.58	0.00
	Rigid	.00	.00	.00	1.34	.17	2.29	3.63	.62	4.90	1.54	.33	.57	.92	0.00
	GVW	3.5	3.8	6.2	26.9	17.1	37.1	62.1	28.7	65.3	56.1	37.0	45.7	53.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9