

Idaho Transportation Department

Monthly WIM Distribution for Jun-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	22	895	712	24	189	82	4	13	302	10	6	4	12	0
	Flex	.00	.00	.00	1.12	.29	.97	1.13	.65	1.79	1.00	1.66	.36	.65	0.00
	Rigid	.00	.00	.00	1.54	.32	1.71	2.03	.82	3.39	2.18	1.83	.37	1.38	0.00
	GVW	4.1	3.7	6.0	28.0	18.3	34.2	50.1	29.0	57.2	57.6	42.2	42.1	56.8	0.0
E	Num	10	503	389	13	89	25	2	7	162	7	3	3	8	0
	Flex	.00	.00	.00	.84	.24	.52	1.60	.38	1.44	1.02	3.09	.55	.80	0.00
	Rigid	.00	.00	.00	1.03	.26	.77	2.68	.44	2.58	2.34	3.48	.58	1.50	0.00
	GVW	4.2	3.6	6.3	25.0	18.3	28.4	56.3	26.9	57.2	61.8	51.5	44.7	61.0	0.0
W	Num	13	393	324	11	100	58	3	7	139	4	3	2	5	0
	Flex	.00	.00	.00	1.53	.35	1.16	.80	.78	2.18	1.22	.24	.18	.37	0.00
	Rigid	.00	.00	.00	2.22	.38	2.12	1.54	1.01	4.29	2.60	.24	.18	1.01	0.00
	GVW	4.1	3.8	5.6	31.6	18.3	36.6	45.2	29.5	57.0	58.5	28.5	37.9	46.4	0.0
E Lane1	Num	10	503	389	13	89	25	2	7	162	7	3	3	8	0
	Flex	.00	.00	.00	.84	.24	.52	1.60	.38	1.44	1.02	3.09	.55	.80	0.00
	Rigid	.00	.00	.00	1.03	.26	.77	2.68	.44	2.58	2.34	3.48	.58	1.50	0.00
	GVW	4.2	3.6	6.3	25.0	18.3	28.4	56.3	26.9	57.2	61.8	51.5	44.7	61.0	0.0
W Lane1	Num	13	393	324	11	100	58	3	7	139	4	3	2	5	0
	Flex	.00	.00	.00	1.53	.35	1.16	.80	.78	2.18	1.22	.24	.18	.37	0.00
	Rigid	.00	.00	.00	2.22	.38	2.12	1.54	1.01	4.29	2.60	.24	.18	1.01	0.00
	GVW	4.1	3.8	5.6	31.6	18.3	36.6	45.2	29.5	57.0	58.5	28.5	37.9	46.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9