

Idaho Transportation Department

Monthly WIM Distribution for Jul-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	17	914	715	16	148	40	5	11	308	16	5	5	26	0
	Flex	.00	.00	.00	.55	.24	.61	.90	.37	1.33	.77	.39	.13	.81	0.00
	Rigid	.00	.00	.00	.66	.26	1.10	1.79	.45	2.53	1.55	.38	.13	1.51	0.00
	GVW	3.7	3.8	5.8	22.1	17.6	29.5	43.3	24.5	53.3	51.3	35.3	34.6	58.8	0.0
E	Num	7	514	389	9	62	13	5	5	162	7	3	3	17	0
	Flex	.00	.00	.00	.34	.17	.34	.93	.19	.83	.64	.43	.10	.87	0.00
	Rigid	.00	.00	.00	.36	.17	.55	1.75	.23	1.46	1.42	.41	.10	1.69	0.00
	GVW	2.9	3.6	6.0	20.2	17.3	26.2	46.6	24.2	50.1	55.6	37.1	33.7	61.9	0.0
W	Num	11	399	327	8	86	28	2	6	146	10	3	3	9	0
	Flex	.00	.00	.00	.85	.29	.78	.81	.46	1.82	.75	.36	.23	.62	0.00
	Rigid	.00	.00	.00	1.07	.32	1.45	1.80	.56	3.58	1.46	.36	.23	1.03	0.00
	GVW	4.1	4.1	5.7	24.8	17.8	31.2	39.2	24.4	56.1	48.9	34.6	37.6	50.2	0.0
E Lane1	Num	7	514	389	9	62	13	5	5	162	7	3	3	17	0
	Flex	.00	.00	.00	.34	.17	.34	.93	.19	.83	.64	.43	.10	.87	0.00
	Rigid	.00	.00	.00	.36	.17	.55	1.75	.23	1.46	1.42	.41	.10	1.69	0.00
	GVW	2.9	3.6	6.0	20.2	17.3	26.2	46.6	24.2	50.1	55.6	37.1	33.7	61.9	0.0
W Lane1	Num	11	399	327	8	86	28	2	6	146	10	3	3	9	0
	Flex	.00	.00	.00	.85	.29	.78	.81	.46	1.82	.75	.36	.23	.62	0.00
	Rigid	.00	.00	.00	1.07	.32	1.45	1.80	.56	3.58	1.46	.36	.23	1.03	0.00
	GVW	4.1	4.1	5.7	24.8	17.8	31.2	39.2	24.4	56.1	48.9	34.6	37.6	50.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9