

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2019

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	677	664	13	156	6	2	15	378	11	8	5	27	0
	Flex	.00	.00	.00	.74	.17	.48	2.68	.43	1.94	.94	.80	.30	1.26	0.00
	Rigid	.00	.00	.00	.88	.18	.69	6.39	.51	3.83	2.30	.84	.33	2.18	0.00
	GVW	1.9	3.8	6.0	22.7	17.6	24.8	49.9	27.0	58.8	59.4	39.9	39.3	62.3	0.0
E	Num	2	381	367	7	58	4	0	7	180	5	4	3	15	0
	Flex	.00	.00	.00	.43	.12	.57	0.00	.23	.75	.41	.43	.13	1.14	0.00
	Rigid	.00	.00	.00	.47	.12	.82	0.00	.26	1.34	1.05	.42	.14	1.85	0.00
	GVW	1.5	3.6	6.3	20.9	16.7	24.0	0.0	25.5	49.9	54.3	39.8	39.7	64.2	0.0
W	Num	1	296	297	6	98	3	2	7	198	5	4	3	13	0
	Flex	.00	.00	.00	1.11	.20	.62	2.68	.58	3.03	1.31	1.16	.36	1.53	0.00
	Rigid	.00	.00	.00	1.38	.21	.96	6.39	.69	6.11	3.00	1.26	.40	2.84	0.00
	GVW	2.4	4.0	5.6	25.2	18.0	29.3	49.9	27.8	66.7	61.4	38.6	36.7	60.2	0.0
E Lane1	Num	2	381	367	7	58	4	0	7	180	5	4	3	15	0
	Flex	.00	.00	.00	.43	.12	.57	0.00	.23	.75	.41	.43	.13	1.14	0.00
	Rigid	.00	.00	.00	.47	.12	.82	0.00	.26	1.34	1.05	.42	.14	1.85	0.00
	GVW	1.5	3.6	6.3	20.9	16.7	24.0	0.0	25.5	49.9	54.3	39.8	39.7	64.2	0.0
W Lane1	Num	1	296	297	6	98	3	2	7	198	5	4	3	13	0
	Flex	.00	.00	.00	1.11	.20	.62	2.68	.58	3.03	1.31	1.16	.36	1.53	0.00
	Rigid	.00	.00	.00	1.38	.21	.96	6.39	.69	6.11	3.00	1.26	.40	2.84	0.00
	GVW	2.4	4.0	5.6	25.2	18.0	29.3	49.9	27.8	66.7	61.4	38.6	36.7	60.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2019

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9