

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2019

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	711	653	16	216	7	2	16	380	12	8	5	29	0
	Flex	.00	.00	.00	1.29	.19	.75	.22	.67	3.03	1.19	1.53	2.05	1.79	0.00
	Rigid	.00	.00	.00	1.51	.20	1.11	.64	.83	5.91	2.66	1.58	2.46	2.86	0.00
	GVW	1.4	4.1	6.9	26.9	17.8	28.4	38.7	29.4	71.9	69.1	53.7	61.2	75.9	0.0
E	Num	1	360	395	7	46	4	1	6	181	6	4	3	15	0
	Flex	.00	.00	.00	.33	.06	.20	.13	.18	.47	.25	.71	.49	.75	0.00
	Rigid	.00	.00	.00	.35	.07	.26	.21	.20	.77	.48	.68	.51	.96	0.00
	GVW	1.3	3.7	6.6	21.9	16.7	21.5	34.8	27.6	50.5	52.7	49.1	55.1	64.8	0.0
W	Num	1	350	267	8	170	4	2	10	199	6	5	3	14	0
	Flex	.00	.00	.00	2.07	.22	1.12	.90	.94	5.26	2.17	2.43	2.52	2.85	0.00
	Rigid	.00	.00	.00	2.44	.23	1.65	2.99	1.17	10.37	4.94	2.58	3.10	4.80	0.00
	GVW	1.5	4.6	7.4	31.1	18.1	33.9	64.7	30.1	90.7	88.4	58.2	58.7	85.1	0.0
E Lane1	Num	1	360	395	7	46	4	1	6	181	6	4	3	15	0
	Flex	.00	.00	.00	.33	.06	.20	.13	.18	.47	.25	.71	.49	.75	0.00
	Rigid	.00	.00	.00	.35	.07	.26	.21	.20	.77	.48	.68	.51	.96	0.00
	GVW	1.3	3.7	6.6	21.9	16.7	21.5	34.8	27.6	50.5	52.7	49.1	55.1	64.8	0.0
W Lane1	Num	1	350	267	8	170	4	2	10	199	6	5	3	14	0
	Flex	.00	.00	.00	2.07	.22	1.12	.90	.94	5.26	2.17	2.43	2.52	2.85	0.00
	Rigid	.00	.00	.00	2.44	.23	1.65	2.99	1.17	10.37	4.94	2.58	3.10	4.80	0.00
	GVW	1.5	4.6	7.4	31.1	18.1	33.9	64.7	30.1	90.7	88.4	58.2	58.7	85.1	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2019

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9