

Idaho Transportation Department

Monthly WIM Distribution for Nov-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	677	576	11	143	7	1	13	380	19	9	6	29	0
	Flex	.00	.00	.00	.52	.12	.51	.35	.70	1.78	.73	1.57	1.44	1.25	0.00
	Rigid	.00	.00	.00	.56	.13	.72	.71	.83	3.32	1.28	1.57	1.61	1.75	0.00
	GVW	3.5	4.2	6.9	23.2	16.4	26.8	49.2	32.6	66.5	63.5	57.7	63.1	74.4	0.0
E	Num	1	332	335	6	27	5	0	6	184	9	5	3	17	0
	Flex	.00	.00	.00	.25	.05	.13	0.00	.19	.55	.31	1.13	.61	.73	0.00
	Rigid	.00	.00	.00	.25	.05	.16	0.00	.21	.83	.65	1.09	.64	.99	0.00
	GVW	4.0	3.6	6.4	21.5	16.2	21.5	0.0	28.6	50.1	61.5	55.3	58.2	69.9	0.0
W	Num	1	345	241	5	116	3	1	7	196	11	4	3	12	0
	Flex	.00	.00	.00	.84	.14	1.03	.35	1.01	2.98	1.03	2.10	2.26	2.06	0.00
	Rigid	.00	.00	.00	.91	.15	1.47	.71	1.20	5.69	1.70	2.16	2.57	2.94	0.00
	GVW	2.5	4.7	7.6	26.0	16.4	34.5	49.2	35.3	81.9	64.3	60.0	67.9	81.3	0.0
E Lane1	Num	1	332	335	6	27	5	0	6	184	9	5	3	17	0
	Flex	.00	.00	.00	.25	.05	.13	0.00	.19	.55	.31	1.13	.61	.73	0.00
	Rigid	.00	.00	.00	.25	.05	.16	0.00	.21	.83	.65	1.09	.64	.99	0.00
	GVW	4.0	3.6	6.4	21.5	16.2	21.5	0.0	28.6	50.1	61.5	55.3	58.2	69.9	0.0
W Lane1	Num	1	345	241	5	116	3	1	7	196	11	4	3	12	0
	Flex	.00	.00	.00	.84	.14	1.03	.35	1.01	2.98	1.03	2.10	2.26	2.06	0.00
	Rigid	.00	.00	.00	.91	.15	1.47	.71	1.20	5.69	1.70	2.16	2.57	2.94	0.00
	GVW	2.5	4.7	7.6	26.0	16.4	34.5	49.2	35.3	81.9	64.3	60.0	67.9	81.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2019

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9