

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2019

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	570	523	9	73	7	0	12	358	9	12	6	16	0
	Flex	.00	.00	.00	.36	.08	.52	0.00	.35	1.01	.43	.96	.89	.83	0.00
	Rigid	.00	.00	.00	.39	.08	.76	0.00	.38	1.84	.94	.96	.96	1.25	0.00
	GVW	2.5	3.8	6.4	21.8	15.8	26.3	0.0	29.7	58.5	60.3	49.6	54.7	66.9	0.0
E	Num	1	282	288	4	12	4	0	6	170	6	6	3	8	0
	Flex	.00	.00	.00	.18	.05	.14	0.00	.14	.26	.15	.51	.24	.38	0.00
	Rigid	.00	.00	.00	.19	.05	.17	0.00	.14	.41	.27	.48	.24	.50	0.00
	GVW	2.2	3.3	5.8	18.8	15.9	21.7	0.0	25.8	44.4	47.2	46.8	47.0	58.0	0.0
W	Num	1	288	235	5	61	3	0	6	188	4	7	3	8	0
	Flex	.00	.00	.00	.54	.09	1.03	0.00	.57	1.70	.76	1.21	1.42	1.29	0.00
	Rigid	.00	.00	.00	.59	.09	1.57	0.00	.62	3.13	1.66	1.22	1.56	2.03	0.00
	GVW	2.6	4.3	7.1	24.7	15.8	33.3	0.0	33.8	71.4	72.0	51.0	61.3	76.1	0.0
E Lane1	Num	1	282	288	4	12	4	0	6	170	6	6	3	8	0
	Flex	.00	.00	.00	.18	.05	.14	0.00	.14	.26	.15	.51	.24	.38	0.00
	Rigid	.00	.00	.00	.19	.05	.17	0.00	.14	.41	.27	.48	.24	.50	0.00
	GVW	2.2	3.3	5.8	18.8	15.9	21.7	0.0	25.8	44.4	47.2	46.8	47.0	58.0	0.0
W Lane1	Num	1	288	235	5	61	3	0	6	188	4	7	3	8	0
	Flex	.00	.00	.00	.54	.09	1.03	0.00	.57	1.70	.76	1.21	1.42	1.29	0.00
	Rigid	.00	.00	.00	.59	.09	1.57	0.00	.62	3.13	1.66	1.22	1.56	2.03	0.00
	GVW	2.6	4.3	7.1	24.7	15.8	33.3	0.0	33.8	71.4	72.0	51.0	61.3	76.1	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2019

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9