

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	433	453	9	55	8	1	11	366	8	13	6	14	0
	Flex	.00	.00	.00	.32	.08	.63	.65	.26	.73	.37	.68	.64	.55	0.00
	Rigid	.00	.00	.00	.38	.08	.94	1.19	.28	1.27	.72	.66	.68	.84	0.00
	GVW	2.1	3.7	6.4	22.4	16.0	29.4	52.0	28.4	54.8	57.0	47.3	53.2	63.4	0.0
E	Num	1	217	241	4	12	4	0	6	179	4	7	3	8	0
	Flex	.00	.00	.00	.13	.04	.19	0.00	.11	.24	.15	.45	.26	.32	0.00
	Rigid	.00	.00	.00	.14	.04	.24	0.00	.12	.37	.27	.42	.26	.41	0.00
	GVW	1.8	3.3	5.8	18.7	15.6	23.4	0.0	25.2	43.2	50.3	46.2	47.9	56.1	0.0
W	Num	1	216	213	4	44	4	1	6	187	4	7	3	7	0
	Flex	.00	.00	.00	.44	.09	1.11	.65	.39	1.22	.60	.87	.96	.80	0.00
	Rigid	.00	.00	.00	.52	.09	1.70	1.19	.43	2.15	1.21	.85	1.01	1.29	0.00
	GVW	1.9	4.1	7.1	24.6	16.1	35.9	52.0	31.2	66.0	64.5	48.3	58.0	70.7	0.0
E Lane1	Num	1	217	241	4	12	4	0	6	179	4	7	3	8	0
	Flex	.00	.00	.00	.13	.04	.19	0.00	.11	.24	.15	.45	.26	.32	0.00
	Rigid	.00	.00	.00	.14	.04	.24	0.00	.12	.37	.27	.42	.26	.41	0.00
	GVW	1.8	3.3	5.8	18.7	15.6	23.4	0.0	25.2	43.2	50.3	46.2	47.9	56.1	0.0
W Lane1	Num	1	216	213	4	44	4	1	6	187	4	7	3	7	0
	Flex	.00	.00	.00	.44	.09	1.11	.65	.39	1.22	.60	.87	.96	.80	0.00
	Rigid	.00	.00	.00	.52	.09	1.70	1.19	.43	2.15	1.21	.85	1.01	1.29	0.00
	GVW	1.9	4.1	7.1	24.6	16.1	35.9	52.0	31.2	66.0	64.5	48.3	58.0	70.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9