

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2020

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	5	441	484	10	113	13	1	13	352	8	8	5	13	0
	Flex	.00	.00	.00	1.23	.15	1.31	.33	.59	2.24	.92	.93	.44	1.37	0.00
	Rigid	.00	.00	.00	1.55	.16	2.25	1.16	.73	4.33	1.76	.95	.48	2.44	0.00
	GVW	3.0	3.9	6.3	25.1	17.3	31.4	44.8	28.1	61.2	59.5	44.6	44.9	67.6	0.0
E	Num	3	239	273	6	42	5	1	6	180	5	4	3	7	0
	Flex	.00	.00	.00	.98	.11	.35	.48	.22	.83	.45	.60	.25	1.09	0.00
	Rigid	.00	.00	.00	1.16	.12	.50	1.55	.25	1.44	.74	.58	.27	1.63	0.00
	GVW	2.8	3.7	6.5	23.7	16.9	25.1	54.2	25.5	52.6	49.0	45.5	46.1	71.4	0.0
W	Num	4	202	211	5	71	9	1	7	172	3	4	3	6	0
	Flex	.00	.00	.00	1.54	.16	2.25	.28	.88	3.54	1.75	1.06	.65	1.38	0.00
	Rigid	.00	.00	.00	2.02	.17	3.86	.96	1.13	6.99	3.58	1.12	.72	2.68	0.00
	GVW	3.7	4.0	6.2	26.8	17.5	38.5	42.6	30.1	69.4	71.1	37.9	43.8	58.3	0.0
E Lane1	Num	3	239	273	6	42	5	1	6	180	5	4	3	7	0
	Flex	.00	.00	.00	.98	.11	.35	.48	.22	.83	.45	.60	.25	1.09	0.00
	Rigid	.00	.00	.00	1.16	.12	.50	1.55	.25	1.44	.74	.58	.27	1.63	0.00
	GVW	2.8	3.7	6.5	23.7	16.9	25.1	54.2	25.5	52.6	49.0	45.5	46.1	71.4	0.0
W Lane1	Num	4	202	211	5	71	9	1	7	172	3	4	3	6	0
	Flex	.00	.00	.00	1.54	.16	2.25	.28	.88	3.54	1.75	1.06	.65	1.38	0.00
	Rigid	.00	.00	.00	2.02	.17	3.86	.96	1.13	6.99	3.58	1.12	.72	2.68	0.00
	GVW	3.7	4.0	6.2	26.8	17.5	38.5	42.6	30.1	69.4	71.1	37.9	43.8	58.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2020

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9