

Idaho Transportation Department

Monthly WIM Distribution for May-2020

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	10	694	637	17	158	34	2	17	361	15	6	6	16	0
	Flex	.00	.00	.00	.96	.16	1.31	1.60	.60	1.63	.99	.78	.56	1.08	0.00
	Rigid	.00	.00	.00	1.24	.17	2.32	3.78	.70	3.05	2.24	.78	.61	1.58	0.00
	GVW	3.3	3.9	6.4	26.3	17.3	34.6	63.1	29.4	58.9	66.9	43.8	47.3	68.9	0.0
E	Num	6	391	363	9	60	10	2	7	186	9	4	4	10	0
	Flex	.00	.00	.00	.58	.10	.35	.49	.27	.76	.70	.67	.30	.85	0.00
	Rigid	.00	.00	.00	.63	.11	.52	1.86	.30	1.34	1.53	.64	.31	1.19	0.00
	GVW	3.1	3.8	6.6	22.6	17.2	25.6	64.5	27.3	53.7	65.6	49.0	47.3	69.4	0.0
W	Num	7	304	273	8	98	25	2	9	175	6	3	3	6	0
	Flex	.00	.00	.00	1.41	.20	2.14	1.79	.77	2.61	1.38	1.05	1.07	1.12	0.00
	Rigid	.00	.00	.00	1.98	.21	3.76	4.12	.93	4.97	3.08	1.09	1.19	1.75	0.00
	GVW	3.7	4.2	6.1	30.8	17.3	42.4	63.7	30.5	64.2	64.6	40.6	51.3	56.3	0.0
E Lane1	Num	6	391	363	9	60	10	2	7	186	9	4	4	10	0
	Flex	.00	.00	.00	.58	.10	.35	.49	.27	.76	.70	.67	.30	.85	0.00
	Rigid	.00	.00	.00	.63	.11	.52	1.86	.30	1.34	1.53	.64	.31	1.19	0.00
	GVW	3.1	3.8	6.6	22.6	17.2	25.6	64.5	27.3	53.7	65.6	49.0	47.3	69.4	0.0
W Lane1	Num	7	304	273	8	98	25	2	9	175	6	3	3	6	0
	Flex	.00	.00	.00	1.41	.20	2.14	1.79	.77	2.61	1.38	1.05	1.07	1.12	0.00
	Rigid	.00	.00	.00	1.98	.21	3.76	4.12	.93	4.97	3.08	1.09	1.19	1.75	0.00
	GVW	3.7	4.2	6.1	30.8	17.3	42.4	63.7	30.5	64.2	64.6	40.6	51.3	56.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2020

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9