

Idaho Transportation Department

Monthly WIM Distribution for Jun-2020

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	15	895	597	24	343	62	6	21	356	13	5	5	14	0
	Flex	.00	.00	.00	2.72	.26	3.59	3.15	.88	2.93	1.91	1.28	.45	1.15	0.00
	Rigid	.00	.00	.00	3.84	.28	6.37	6.32	1.08	5.46	3.94	1.30	.48	2.08	0.00
	GVW	3.7	4.8	6.8	34.8	18.6	47.2	71.6	30.0	67.9	73.4	48.4	45.8	69.4	0.0
E	Num	7	480	309	12	185	15	6	11	187	7	3	3	11	0
	Flex	.00	.00	.00	2.40	.20	1.68	4.34	.52	2.85	2.16	1.91	.39	1.39	0.00
	Rigid	.00	.00	.00	2.95	.21	2.61	8.14	.64	5.28	4.33	1.94	.42	2.24	0.00
	GVW	4.0	5.0	7.1	32.1	18.1	38.5	78.0	27.5	68.7	80.7	58.8	47.2	76.4	0.0
W	Num	8	415	288	12	158	47	2	10	169	5	4	2	4	0
	Flex	.00	.00	.00	3.31	.31	4.35	3.58	1.07	3.12	1.83	.85	.68	.91	0.00
	Rigid	.00	.00	.00	5.13	.34	7.82	7.86	1.31	5.87	3.73	.86	.74	2.57	0.00
	GVW	4.0	4.7	6.6	37.8	18.9	50.1	72.1	31.9	67.4	63.5	41.8	49.7	53.4	0.0
E Lane1	Num	7	480	309	12	185	15	6	11	187	7	3	3	11	0
	Flex	.00	.00	.00	2.40	.20	1.68	4.34	.52	2.85	2.16	1.91	.39	1.39	0.00
	Rigid	.00	.00	.00	2.95	.21	2.61	8.14	.64	5.28	4.33	1.94	.42	2.24	0.00
	GVW	4.0	5.0	7.1	32.1	18.1	38.5	78.0	27.5	68.7	80.7	58.8	47.2	76.4	0.0
W Lane1	Num	8	415	288	12	158	47	2	10	169	5	4	2	4	0
	Flex	.00	.00	.00	3.31	.31	4.35	3.58	1.07	3.12	1.83	.85	.68	.91	0.00
	Rigid	.00	.00	.00	5.13	.34	7.82	7.86	1.31	5.87	3.73	.86	.74	2.57	0.00
	GVW	4.0	4.7	6.6	37.8	18.9	50.1	72.1	31.9	67.4	63.5	41.8	49.7	53.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2020

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9