

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2020

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1,225	1,010	610	26	418	70	5	22	318	7	5	5	11	0
	Flex	.08	.00	.00	3.46	.26	4.48	3.82	.86	3.22	3.55	1.83	.33	1.40	0.00
	Rigid	.14	.00	.00	4.74	.27	8.08	7.92	1.08	5.94	7.90	1.92	.35	2.69	0.00
	GVW	8.7	4.9	6.6	36.9	18.4	53.8	74.0	29.2	68.0	87.1	48.2	43.0	63.1	0.0
E	Num	623	520	323	13	203	20	3	11	172	4	3	4	7	0
	Flex	.05	.00	.00	3.67	.22	2.61	4.05	.91	3.31	4.45	2.01	.22	2.11	0.00
	Rigid	.08	.00	.00	4.63	.23	4.05	7.58	1.19	6.06	9.23	2.08	.24	3.67	0.00
	GVW	8.3	5.0	6.7	36.0	18.0	43.6	69.6	29.2	68.5	87.6	51.3	40.2	77.7	0.0
W	Num	602	490	288	13	215	50	2	11	146	3	4	3	5	0
	Flex	.11	.00	.00	3.94	.26	5.54	3.46	.68	3.50	2.54	1.20	.32	.72	0.00
	Rigid	.20	.00	.00	5.88	.28	10.15	8.39	.80	6.52	6.54	1.23	.33	1.71	0.00
	GVW	9.2	5.0	6.5	39.5	18.5	59.3	78.7	29.1	68.7	84.2	45.2	38.8	48.0	0.0
E Lane1	Num	623	520	323	13	203	20	3	11	172	4	3	4	7	0
	Flex	.05	.00	.00	3.67	.22	2.61	4.05	.91	3.31	4.45	2.01	.22	2.11	0.00
	Rigid	.08	.00	.00	4.63	.23	4.05	7.58	1.19	6.06	9.23	2.08	.24	3.67	0.00
	GVW	8.3	5.0	6.7	36.0	18.0	43.6	69.6	29.2	68.5	87.6	51.3	40.2	77.7	0.0
W Lane1	Num	602	490	288	13	215	50	2	11	146	3	4	3	5	0
	Flex	.11	.00	.00	3.94	.26	5.54	3.46	.68	3.50	2.54	1.20	.32	.72	0.00
	Rigid	.20	.00	.00	5.88	.28	10.15	8.39	.80	6.52	6.54	1.23	.33	1.71	0.00
	GVW	9.2	5.0	6.5	39.5	18.5	59.3	78.7	29.1	68.7	84.2	45.2	38.8	48.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2020

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9