

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2023

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	755	320	4	29	24	2	24	349	10	13	7	7	0
	Flex	.03	.01	.00	.81	.37	.42	.61	.41	1.49	.84	2.07	1.62	2.32	0.00
	Rigid	.06	.01	.00	1.18	.37	.83	1.62	.51	2.88	2.12	2.08	2.25	4.03	0.00
	GVW	13.1	6.2	5.5	41.7	19.2	36.5	61.0	31.2	71.7	82.8	63.2	75.4	99.5	0.0
E	Num	2	486	73	2	10	8	2	9	157	4	4	3	3	0
	Flex	.03	.01	.01	1.09	.61	.46	.43	.87	1.72	1.08	4.16	1.92	2.66	0.00
	Rigid	.07	.01	.01	1.55	.61	1.01	1.26	1.09	3.35	2.79	4.32	2.37	4.64	0.00
	GVW	12.1	7.9	8.2	45.3	22.4	43.6	54.6	41.1	73.9	93.5	74.4	73.8	101.2	0.0
W	Num	8	270	247	3	18	16	2	15	192	6	9	4	4	0
	Flex	.02	.01	.00	.65	.22	.39	.68	.18	1.28	.70	1.43	1.47	1.91	0.00
	Rigid	.05	.01	.00	.98	.22	.71	1.78	.22	2.48	1.69	1.39	2.30	3.27	0.00
	GVW	13.0	2.9	4.7	39.0	17.3	32.7	65.0	25.9	69.7	76.7	60.1	76.5	95.4	0.0
E Lane1	Num	2	486	73	2	10	8	2	9	157	4	4	3	3	0
	Flex	.03	.01	.01	1.09	.61	.46	.43	.87	1.72	1.08	4.16	1.92	2.66	0.00
	Rigid	.07	.01	.01	1.55	.61	1.01	1.26	1.09	3.35	2.79	4.32	2.37	4.64	0.00
	GVW	12.1	7.9	8.2	45.3	22.4	43.6	54.6	41.1	73.9	93.5	74.4	73.8	101.2	0.0
W Lane1	Num	8	270	247	3	18	16	2	15	192	6	9	4	4	0
	Flex	.02	.01	.00	.65	.22	.39	.68	.18	1.28	.70	1.43	1.47	1.91	0.00
	Rigid	.05	.01	.00	.98	.22	.71	1.78	.22	2.48	1.69	1.39	2.30	3.27	0.00
	GVW	13.0	2.9	4.7	39.0	17.3	32.7	65.0	25.9	69.7	76.7	60.1	76.5	95.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2023

Site names: 00138  
 County: Owyhee  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4  
 Daily Factor Grp: 4  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9