

Idaho Transportation Department

Monthly WIM Distribution for May-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,111	818	7	68	20	2	63	450	34	7	10	19	0
	Flex	1.60	.01	.01	1.03	.42	.41	.39	.26	1.23	.89	2.03	1.16	2.04	0.00
	Rigid	4.00	.01	.01	1.46	.43	.69	1.12	.32	2.36	2.32	2.04	1.43	2.51	0.00
	GVW	18.2	3.3	5.5	44.2	19.7	31.6	50.7	24.9	66.6	85.1	62.2	68.8	87.4	0.0
E	Num	1	554	400	3	35	7	2	35	221	18	4	5	9	0
	Flex	2.15	.01	.02	1.62	.59	.33	.38	.35	1.43	1.07	3.34	1.50	2.96	0.00
	Rigid	5.39	.01	.02	2.29	.61	.50	1.03	.45	2.73	2.91	3.43	1.90	3.56	0.00
	GVW	15.8	3.9	6.2	48.3	21.8	31.2	48.8	26.6	70.4	95.6	73.3	75.0	98.1	0.0
W	Num	2	556	417	4	33	14	2	28	229	16	4	5	10	0
	Flex	.14	.00	.00	.57	.26	.44	.40	.14	1.04	.65	.89	.79	1.20	0.00
	Rigid	.29	.01	.00	.82	.26	.78	1.13	.16	1.99	1.55	.85	.98	1.60	0.00
	GVW	15.2	2.7	4.8	41.2	17.5	31.7	50.9	22.9	62.9	72.0	51.4	63.9	77.2	0.0
E Lane1	Num	1	554	400	3	35	7	2	35	221	18	4	5	9	0
	Flex	2.15	.01	.02	1.62	.59	.33	.38	.35	1.43	1.07	3.34	1.50	2.96	0.00
	Rigid	5.39	.01	.02	2.29	.61	.50	1.03	.45	2.73	2.91	3.43	1.90	3.56	0.00
	GVW	15.8	3.9	6.2	48.3	21.8	31.2	48.8	26.6	70.4	95.6	73.3	75.0	98.1	0.0
W Lane1	Num	2	556	417	4	33	14	2	28	229	16	4	5	10	0
	Flex	.14	.00	.00	.57	.26	.44	.40	.14	1.04	.65	.89	.79	1.20	0.00
	Rigid	.29	.01	.00	.82	.26	.78	1.13	.16	1.99	1.55	.85	.98	1.60	0.00
	GVW	15.2	2.7	4.8	41.2	17.5	31.7	50.9	22.9	62.9	72.0	51.4	63.9	77.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9