

Idaho Transportation Department

Monthly WIM Distribution for Jul-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	1,264	872	7	75	24	5	56	449	70	5	12	44	0
	Flex	.41	.00	.00	1.86	.31	.36	.26	.18	.99	.63	1.17	.93	1.45	0.00
	Rigid	.95	.00	.00	2.38	.31	.58	.60	.22	1.86	1.53	1.13	1.09	2.14	0.00
	GVW	11.5	3.1	5.2	40.6	19.1	30.6	44.6	24.9	63.5	77.8	56.3	65.4	91.4	0.0
E	Num	2	637	433	3	37	10	5	28	220	37	3	6	22	0
	Flex	1.20	.00	.00	4.71	.35	.33	.32	.19	.92	.66	1.63	1.14	1.27	0.00
	Rigid	2.78	.00	.00	5.83	.34	.49	.74	.24	1.71	1.57	1.57	1.31	1.53	0.00
	GVW	17.7	3.4	5.7	46.2	20.6	32.0	47.8	26.1	64.8	82.1	63.2	69.9	84.5	0.0
W	Num	2	628	439	4	38	14	2	28	228	33	3	5	22	0
	Flex	.01	.00	.00	.89	.27	.37	.15	.17	1.04	.64	.72	.86	1.53	0.00
	Rigid	.03	.00	.00	1.22	.27	.62	.36	.20	2.00	1.57	.69	1.04	2.59	0.00
	GVW	9.0	2.7	4.7	37.8	17.4	29.0	40.0	23.8	62.2	75.0	49.2	63.5	97.6	0.0
E Lane1	Num	2	637	433	3	37	10	5	28	220	37	3	6	22	0
	Flex	1.20	.00	.00	4.71	.35	.33	.32	.19	.92	.66	1.63	1.14	1.27	0.00
	Rigid	2.78	.00	.00	5.83	.34	.49	.74	.24	1.71	1.57	1.57	1.31	1.53	0.00
	GVW	17.7	3.4	5.7	46.2	20.6	32.0	47.8	26.1	64.8	82.1	63.2	69.9	84.5	0.0
W Lane1	Num	2	628	439	4	38	14	2	28	228	33	3	5	22	0
	Flex	.01	.00	.00	.89	.27	.37	.15	.17	1.04	.64	.72	.86	1.53	0.00
	Rigid	.03	.00	.00	1.22	.27	.62	.36	.20	2.00	1.57	.69	1.04	2.59	0.00
	GVW	9.0	2.7	4.7	37.8	17.4	29.0	40.0	23.8	62.2	75.0	49.2	63.5	97.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9