

Idaho Transportation Department

Monthly WIM Distribution for Aug-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,114	823	9	79	35	8	57	449	89	6	14	45	0
	Flex	2.16	.00	.01	2.78	.39	.32	.37	.26	1.14	.85	1.35	1.20	1.92	0.00
	Rigid	5.38	.01	.01	3.52	.39	.47	.67	.34	2.18	2.26	1.30	1.45	3.00	0.00
	GVW	18.7	3.2	5.4	42.6	19.3	30.9	45.5	25.6	66.3	88.6	58.3	69.5	102.5	0.0
E	Num	1	574	413	5	37	17	7	29	223	46	3	8	22	0
	Flex	3.75	.01	.02	4.52	.47	.43	.64	.37	1.16	.80	1.87	1.44	2.07	0.00
	Rigid	9.35	.01	.02	5.68	.48	.64	1.12	.50	2.17	2.08	1.82	1.79	2.81	0.00
	GVW	25.4	3.5	5.9	45.5	20.7	34.2	51.9	27.7	67.2	86.8	65.5	73.1	98.3	0.0
W	Num	2	540	409	5	42	18	4	28	226	43	3	7	23	0
	Flex	.21	.00	.00	1.65	.32	.24	.18	.14	1.14	.86	.72	.89	1.73	0.00
	Rigid	.47	.00	.00	2.11	.31	.36	.41	.17	2.21	2.35	.68	1.08	3.13	0.00
	GVW	11.4	2.8	4.8	40.1	18.1	28.6	42.0	23.5	65.4	89.4	50.0	65.8	105.5	0.0
E Lane1	Num	1	574	413	5	37	17	7	29	223	46	3	8	22	0
	Flex	3.75	.01	.02	4.52	.47	.43	.64	.37	1.16	.80	1.87	1.44	2.07	0.00
	Rigid	9.35	.01	.02	5.68	.48	.64	1.12	.50	2.17	2.08	1.82	1.79	2.81	0.00
	GVW	25.4	3.5	5.9	45.5	20.7	34.2	51.9	27.7	67.2	86.8	65.5	73.1	98.3	0.0
W Lane1	Num	2	540	409	5	42	18	4	28	226	43	3	7	23	0
	Flex	.21	.00	.00	1.65	.32	.24	.18	.14	1.14	.86	.72	.89	1.73	0.00
	Rigid	.47	.00	.00	2.11	.31	.36	.41	.17	2.21	2.35	.68	1.08	3.13	0.00
	GVW	11.4	2.8	4.8	40.1	18.1	28.6	42.0	23.5	65.4	89.4	50.0	65.8	105.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9