

Idaho Transportation Department

Monthly WIM Distribution for Oct-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,060	810	8	69	14	2	58	455	19	7	12	23	0
	Flex	.98	.00	.01	1.20	.34	.32	.50	.33	1.35	.84	2.04	1.40	2.13	0.00
	Rigid	2.32	.00	.01	1.70	.34	.52	1.09	.43	2.60	2.11	2.01	1.72	2.81	0.00
	GVW	19.4	3.4	5.4	45.6	19.5	31.0	54.7	26.8	69.8	84.6	65.4	72.7	90.8	0.0
E	Num	1	581	389	3	32	7	1	29	226	8	4	6	11	0
	Flex	2.44	.00	.01	1.31	.41	.35	.66	.49	1.34	.96	2.44	1.90	3.11	0.00
	Rigid	5.92	.01	.01	1.70	.41	.53	1.62	.65	2.55	2.34	2.41	2.33	3.90	0.00
	GVW	25.1	4.0	5.9	43.9	20.5	31.7	66.8	28.7	69.4	81.4	68.8	78.1	97.7	0.0
W	Num	2	479	420	5	37	7	2	28	229	11	3	6	13	0
	Flex	.24	.00	.00	1.14	.29	.32	.45	.17	1.36	.79	1.32	1.01	1.25	0.00
	Rigid	.50	.00	.00	1.78	.29	.52	.98	.19	2.66	2.01	1.29	1.25	1.91	0.00
	GVW	17.8	2.7	5.0	46.9	18.6	30.6	54.2	24.9	70.3	86.2	58.8	68.0	85.0	0.0
E Lane1	Num	1	581	389	3	32	7	1	29	226	8	4	6	11	0
	Flex	2.44	.00	.01	1.31	.41	.35	.66	.49	1.34	.96	2.44	1.90	3.11	0.00
	Rigid	5.92	.01	.01	1.70	.41	.53	1.62	.65	2.55	2.34	2.41	2.33	3.90	0.00
	GVW	25.1	4.0	5.9	43.9	20.5	31.7	66.8	28.7	69.4	81.4	68.8	78.1	97.7	0.0
W Lane1	Num	2	479	420	5	37	7	2	28	229	11	3	6	13	0
	Flex	.24	.00	.00	1.14	.29	.32	.45	.17	1.36	.79	1.32	1.01	1.25	0.00
	Rigid	.50	.00	.00	1.78	.29	.52	.98	.19	2.66	2.01	1.29	1.25	1.91	0.00
	GVW	17.8	2.7	5.0	46.9	18.6	30.6	54.2	24.9	70.3	86.2	58.8	68.0	85.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9