

Idaho Transportation Department

Monthly WIM Distribution for Nov-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,210	606	6	56	16	2	43	422	37	8	11	19	0
	Flex	.16	.01	.01	1.24	.37	.64	.28	.39	1.48	.83	3.40	2.74	3.11	0.00
	Rigid	.37	.01	.01	1.66	.37	1.14	.81	.51	2.93	2.06	3.60	3.47	4.23	0.00
	GVW	13.3	4.5	5.6	39.6	19.4	35.5	49.6	29.2	70.6	84.4	70.4	79.3	101.3	0.0
E	Num	3	679	244	2	23	7	2	20	206	18	4	5	10	0
	Flex	.04	.01	.02	1.04	.36	.60	.29	.53	1.30	.81	2.52	2.83	3.16	0.00
	Rigid	.09	.01	.02	1.42	.36	1.05	.91	.72	2.52	2.01	2.50	3.58	3.98	0.00
	GVW	9.6	5.4	6.4	42.6	20.1	35.3	52.5	31.7	69.2	87.0	69.3	79.3	102.4	0.0
W	Num	2	531	361	4	33	9	1	22	216	19	4	5	9	0
	Flex	.38	.01	.00	1.31	.36	.67	.41	.26	1.64	.81	4.26	2.59	3.07	0.00
	Rigid	.84	.01	.00	1.81	.37	1.22	1.04	.33	3.29	2.03	4.65	3.29	4.43	0.00
	GVW	18.8	3.2	5.1	39.2	18.8	35.5	53.0	27.2	71.7	81.2	72.7	77.8	100.3	0.0
E Lane1	Num	3	679	244	2	23	7	2	20	206	18	4	5	10	0
	Flex	.04	.01	.02	1.04	.36	.60	.29	.53	1.30	.81	2.52	2.83	3.16	0.00
	Rigid	.09	.01	.02	1.42	.36	1.05	.91	.72	2.52	2.01	2.50	3.58	3.98	0.00
	GVW	9.6	5.4	6.4	42.6	20.1	35.3	52.5	31.7	69.2	87.0	69.3	79.3	102.4	0.0
W Lane1	Num	2	531	361	4	33	9	1	22	216	19	4	5	9	0
	Flex	.38	.01	.00	1.31	.36	.67	.41	.26	1.64	.81	4.26	2.59	3.07	0.00
	Rigid	.84	.01	.00	1.81	.37	1.22	1.04	.33	3.29	2.03	4.65	3.29	4.43	0.00
	GVW	18.8	3.2	5.1	39.2	18.8	35.5	53.0	27.2	71.7	81.2	72.7	77.8	100.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2023

Site names: 00138
 County: Owyhee
 Funct Class: R Principal Arterial - Other
 Location: US-95 3.6 Mi. S of Jct SH-55

Seasonal Factor Grp: 4
 Daily Factor Grp: 4
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9