

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2015

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	6	940	797	11	111	34	2	8	211	139	1	1	32	0
	Flex	.00	.00	.00	.33	.32	.51	.30	.29	.51	.50	.64	.14	.71	0.00
	Rigid	.00	.00	.00	.40	.31	.69	.65	.30	.92	1.12	.62	.14	1.43	0.00
	GVW	5.3	3.4	5.8	23.4	19.6	31.0	45.2	29.0	45.5	67.3	46.7	35.5	75.9	0.0
E	Num	3	451	384	5	42	14	2	4	110	59	1	1	20	0
	Flex	.00	.00	.00	.42	.18	.43	.56	.39	.55	.50	.77	.14	.35	0.00
	Rigid	.00	.00	.00	.54	.18	.70	1.05	.41	1.03	1.07	.75	.14	.93	0.00
	GVW	5.2	3.4	5.8	25.0	16.4	29.3	42.8	28.7	43.0	57.8	50.9	34.0	66.9	0.0
W	Num	4	489	413	7	69	20	2	5	101	80	1	1	13	0
	Flex	.00	.00	.00	.26	.38	.52	.22	.21	.47	.49	.33	.14	1.18	0.00
	Rigid	.00	.00	.00	.30	.37	.62	.53	.22	.81	1.15	.31	.14	2.00	0.00
	GVW	5.8	3.3	5.7	23.1	21.0	31.2	44.7	28.0	48.6	74.2	40.9	37.0	84.1	0.0
E Lane1	Num	3	451	384	5	42	14	2	4	110	59	1	1	20	0
	Flex	.00	.00	.00	.42	.18	.43	.56	.39	.55	.50	.77	.14	.35	0.00
	Rigid	.00	.00	.00	.54	.18	.70	1.05	.41	1.03	1.07	.75	.14	.93	0.00
	GVW	5.2	3.4	5.8	25.0	16.4	29.3	42.8	28.7	43.0	57.8	50.9	34.0	66.9	0.0
W Lane1	Num	4	489	413	7	69	20	2	5	101	80	1	1	13	0
	Flex	.00	.00	.00	.26	.38	.52	.22	.21	.47	.49	.33	.14	1.18	0.00
	Rigid	.00	.00	.00	.30	.37	.62	.53	.22	.81	1.15	.31	.14	2.00	0.00
	GVW	5.8	3.3	5.7	23.1	21.0	31.2	44.7	28.0	48.6	74.2	40.9	37.0	84.1	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2015

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9