

Idaho Transportation Department

Monthly WIM Distribution for Mar-2015

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	8	959	819	9	86	50	3	11	116	83	2	2	23	0
	Flex	.00	.00	.00	.53	.19	.49	.25	.43	.47	.53	1.24	.96	.60	0.00
	Rigid	.00	.00	.00	.63	.20	.72	.80	.47	.82	1.28	1.22	1.02	1.64	0.00
	GVW	5.6	3.4	5.9	26.1	17.0	29.9	44.8	28.0	43.3	71.2	54.8	52.8	77.8	0.0
E	Num	4	460	397	4	44	23	2	4	59	36	2	1	16	0
	Flex	.00	.00	.00	.55	.23	.43	.34	.57	.54	.73	1.09	1.86	.55	0.00
	Rigid	.00	.00	.00	.67	.24	.72	1.24	.62	.94	1.75	1.05	2.03	1.67	0.00
	GVW	5.6	3.4	5.9	26.7	17.1	28.2	49.2	28.5	43.3	72.0	55.6	64.0	78.8	0.0
W	Num	4	499	423	5	41	27	2	6	56	47	2	1	7	0
	Flex	.00	.00	.00	.49	.14	.51	.24	.36	.39	.39	1.59	.35	.89	0.00
	Rigid	.00	.00	.00	.56	.15	.69	.70	.40	.69	.95	1.63	.35	1.63	0.00
	GVW	5.5	3.3	5.8	25.3	16.8	30.6	39.4	27.5	43.4	70.5	53.2	43.4	72.7	0.0
E Lane1	Num	4	460	397	4	44	23	2	4	59	36	2	1	16	0
	Flex	.00	.00	.00	.55	.23	.43	.34	.57	.54	.73	1.09	1.86	.55	0.00
	Rigid	.00	.00	.00	.67	.24	.72	1.24	.62	.94	1.75	1.05	2.03	1.67	0.00
	GVW	5.6	3.4	5.9	26.7	17.1	28.2	49.2	28.5	43.3	72.0	55.6	64.0	78.8	0.0
W Lane1	Num	4	499	423	5	41	27	2	6	56	47	2	1	7	0
	Flex	.00	.00	.00	.49	.14	.51	.24	.36	.39	.39	1.59	.35	.89	0.00
	Rigid	.00	.00	.00	.56	.15	.69	.70	.40	.69	.95	1.63	.35	1.63	0.00
	GVW	5.5	3.3	5.8	25.3	16.8	30.6	39.4	27.5	43.4	70.5	53.2	43.4	72.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2015

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9