

Idaho Transportation Department

Monthly WIM Distribution for Apr-2015

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	10	1,009	864	17	96	47	3	11	119	85	2	1	24	0
	Flex	.00	.00	.00	.69	.20	.62	.36	.49	.50	.56	.85	.32	.62	0.00
	Rigid	.00	.00	.00	.82	.20	.97	1.17	.56	.90	1.35	.82	.33	1.62	0.00
	GVW	5.3	3.4	6.0	25.8	16.7	31.5	47.7	28.2	43.3	71.4	50.0	47.4	74.9	0.0
E	Num	6	482	421	9	47	22	2	5	59	36	1	1	18	0
	Flex	.00	.00	.00	.81	.21	.57	.27	.36	.60	.74	.94	.36	.67	0.00
	Rigid	.00	.00	.00	.96	.21	.97	.98	.41	1.10	1.78	.90	.38	1.83	0.00
	GVW	5.3	3.4	6.0	26.9	16.6	31.3	48.6	27.8	44.3	73.2	51.9	52.5	79.5	0.0
W	Num	4	527	443	8	50	25	2	6	60	49	1	1	6	0
	Flex	.00	.00	.00	.48	.19	.69	.46	.59	.41	.44	.71	.39	.65	0.00
	Rigid	.00	.00	.00	.57	.20	1.01	1.54	.68	.72	1.05	.68	.39	1.21	0.00
	GVW	5.3	3.4	6.0	24.2	16.7	31.7	50.0	28.1	42.7	70.0	47.4	46.3	64.4	0.0
E Lane1	Num	6	482	421	9	47	22	2	5	59	36	1	1	18	0
	Flex	.00	.00	.00	.81	.21	.57	.27	.36	.60	.74	.94	.36	.67	0.00
	Rigid	.00	.00	.00	.96	.21	.97	.98	.41	1.10	1.78	.90	.38	1.83	0.00
	GVW	5.3	3.4	6.0	26.9	16.6	31.3	48.6	27.8	44.3	73.2	51.9	52.5	79.5	0.0
W Lane1	Num	4	527	443	8	50	25	2	6	60	49	1	1	6	0
	Flex	.00	.00	.00	.48	.19	.69	.46	.59	.41	.44	.71	.39	.65	0.00
	Rigid	.00	.00	.00	.57	.20	1.01	1.54	.68	.72	1.05	.68	.39	1.21	0.00
	GVW	5.3	3.4	6.0	24.2	16.7	31.7	50.0	28.1	42.7	70.0	47.4	46.3	64.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2015

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9