

# Idaho Transportation Department

## Monthly WIM Distribution for May-2015

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	11	1,002	838	11	127	42	6	12	109	95	2	2	23	0
	Flex	.00	.00	.00	1.37	.26	.93	.46	.60	.69	.66	.63	1.67	1.08	0.00
	Rigid	.00	.00	.00	1.84	.28	1.49	1.46	.74	1.26	1.57	.61	1.79	3.31	0.00
	GVW	5.0	3.5	5.8	28.7	16.8	32.8	48.7	28.0	42.4	67.5	46.6	62.8	82.8	0.0
E	Num	7	480	408	6	62	21	2	5	56	37	2	1	19	0
	Flex	.00	.00	.00	1.58	.23	.91	.45	.55	.78	.86	.60	2.78	1.14	0.00
	Rigid	.00	.00	.00	2.07	.24	1.57	1.53	.66	1.48	2.14	.58	3.00	3.58	0.00
	GVW	4.7	3.5	5.8	29.1	16.5	32.8	47.2	27.3	42.5	65.7	48.1	77.4	85.6	0.0
W	Num	4	522	430	6	65	21	5	8	53	58	1	1	4	0
	Flex	.00	.00	.00	1.23	.30	.91	.49	.60	.58	.55	.63	.65	1.02	0.00
	Rigid	.00	.00	.00	1.87	.33	1.31	1.44	.73	1.02	1.29	.61	.68	2.61	0.00
	GVW	5.5	3.5	5.9	29.8	17.2	32.4	51.2	28.3	42.5	69.2	44.0	46.3	67.1	0.0
E Lane1	Num	7	480	408	6	62	21	2	5	56	37	2	1	19	0
	Flex	.00	.00	.00	1.58	.23	.91	.45	.55	.78	.86	.60	2.78	1.14	0.00
	Rigid	.00	.00	.00	2.07	.24	1.57	1.53	.66	1.48	2.14	.58	3.00	3.58	0.00
	GVW	4.7	3.5	5.8	29.1	16.5	32.8	47.2	27.3	42.5	65.7	48.1	77.4	85.6	0.0
W Lane1	Num	4	522	430	6	65	21	5	8	53	58	1	1	4	0
	Flex	.00	.00	.00	1.23	.30	.91	.49	.60	.58	.55	.63	.65	1.02	0.00
	Rigid	.00	.00	.00	1.87	.33	1.31	1.44	.73	1.02	1.29	.61	.68	2.61	0.00
	GVW	5.5	3.5	5.9	29.8	17.2	32.4	51.2	28.3	42.5	69.2	44.0	46.3	67.1	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for May-2015

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9