

Idaho Transportation Department

Monthly WIM Distribution for Apr-2017

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	967	908	11	62	27	1	12	89	73	2	2	46	0
	Flex	.00	.00	.00	.30	.11	.30	.13	.23	.28	.31	.57	.72	.37	0.00
	Rigid	.00	.00	.00	.38	.11	.40	.40	.24	.45	.69	.55	.77	.73	0.00
	GVW	3.1	3.4	5.9	25.8	16.5	26.3	42.2	25.8	39.8	65.7	43.4	46.6	64.4	0.0
E	Num	2	470	450	5	28	15	1	6	51	22	1	1	32	0
	Flex	.00	.00	.00	.33	.09	.28	.15	.27	.24	.28	.48	.31	.28	0.00
	Rigid	.00	.00	.00	.44	.09	.42	.58	.28	.38	.64	.45	.32	.62	0.00
	GVW	1.9	3.3	5.7	27.0	16.1	28.1	47.1	26.2	38.0	63.6	45.0	47.1	59.8	0.0
W	Num	2	498	458	6	34	15	1	7	38	51	1	1	14	0
	Flex	.00	.00	.00	.29	.13	.33	.12	.19	.36	.31	.75	1.15	.58	0.00
	Rigid	.00	.00	.00	.34	.13	.41	.23	.20	.59	.70	.73	1.26	.97	0.00
	GVW	3.2	3.6	6.1	25.5	16.7	26.1	37.4	25.3	43.5	65.8	45.8	50.0	72.7	0.0
E Lane1	Num	2	470	450	5	28	15	1	6	51	22	1	1	32	0
	Flex	.00	.00	.00	.33	.09	.28	.15	.27	.24	.28	.48	.31	.28	0.00
	Rigid	.00	.00	.00	.44	.09	.42	.58	.28	.38	.64	.45	.32	.62	0.00
	GVW	1.9	3.3	5.7	27.0	16.1	28.1	47.1	26.2	38.0	63.6	45.0	47.1	59.8	0.0
W Lane1	Num	2	498	458	6	34	15	1	7	38	51	1	1	14	0
	Flex	.00	.00	.00	.29	.13	.33	.12	.19	.36	.31	.75	1.15	.58	0.00
	Rigid	.00	.00	.00	.34	.13	.41	.23	.20	.59	.70	.73	1.26	.97	0.00
	GVW	3.2	3.6	6.1	25.5	16.7	26.1	37.4	25.3	43.5	65.8	45.8	50.0	72.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2017

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9