

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	984	839	8	123	29	2	14	84	111	2	2	73	0
	Flex	.00	.00	.00	.86	.15	1.23	.22	.63	.68	.71	2.85	.49	1.64	0.00
	Rigid	.00	.00	.00	1.13	.15	1.97	.75	.75	1.14	1.66	3.09	.50	2.99	0.00
	GVW	3.1	3.8	6.1	28.7	16.2	35.2	37.3	28.7	42.7	68.7	60.9	44.7	74.8	0.0
E	Num	3	478	416	4	56	14	2	6	50	42	1	1	47	0
	Flex	.00	.00	.00	.82	.15	1.24	.20	.49	.57	.66	.74	.26	2.16	0.00
	Rigid	.00	.00	.00	1.12	.15	2.08	.73	.63	.96	1.69	.70	.27	3.94	0.00
	GVW	3.8	3.6	5.9	28.7	16.2	35.3	33.5	25.9	39.7	60.2	50.6	43.8	76.1	0.0
W	Num	3	506	424	5	67	18	1	9	34	69	1	1	25	0
	Flex	.00	.00	.00	.90	.14	1.07	.32	.70	.85	.79	3.68	.88	.98	0.00
	Rigid	.00	.00	.00	1.14	.15	1.61	1.02	.80	1.43	1.78	4.02	.90	1.73	0.00
	GVW	2.5	3.9	6.3	28.8	16.4	34.8	43.8	30.1	47.5	74.4	63.9	45.7	71.1	0.0
E Lane1	Num	3	478	416	4	56	14	2	6	50	42	1	1	47	0
	Flex	.00	.00	.00	.82	.15	1.24	.20	.49	.57	.66	.74	.26	2.16	0.00
	Rigid	.00	.00	.00	1.12	.15	2.08	.73	.63	.96	1.69	.70	.27	3.94	0.00
	GVW	3.8	3.6	5.9	28.7	16.2	35.3	33.5	25.9	39.7	60.2	50.6	43.8	76.1	0.0
W Lane1	Num	3	506	424	5	67	18	1	9	34	69	1	1	25	0
	Flex	.00	.00	.00	.90	.14	1.07	.32	.70	.85	.79	3.68	.88	.98	0.00
	Rigid	.00	.00	.00	1.14	.15	1.61	1.02	.80	1.43	1.78	4.02	.90	1.73	0.00
	GVW	2.5	3.9	6.3	28.8	16.4	34.8	43.8	30.1	47.5	74.4	63.9	45.7	71.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9