

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2017

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	6	956	781	8	174	32	3	16	79	91	1	1	49	0
	Flex	.00	.00	.00	2.05	.19	1.65	1.68	.86	.77	.86	2.54	.37	1.41	0.00
	Rigid	.00	.00	.00	2.97	.20	2.65	4.40	1.13	1.33	2.17	2.76	.38	2.98	0.00
	GVW	1.9	3.8	5.7	38.8	16.1	36.8	62.4	30.0	40.6	72.1	54.1	35.1	73.8	0.0
E	Num	3	480	416	3	59	16	2	5	45	35	1	1	38	0
	Flex	.00	.00	.00	1.67	.15	.94	.34	.59	.58	.73	.34	.09	.88	0.00
	Rigid	.00	.00	.00	2.38	.15	1.62	1.06	.82	1.00	1.84	.31	.09	2.20	0.00
	GVW	3.3	3.4	5.5	37.4	16.0	32.5	50.5	26.6	37.2	63.5	39.5	27.5	70.0	0.0
W	Num	5	494	375	5	117	16	2	11	37	59	1	1	15	0
	Flex	.00	.00	.00	1.88	.20	2.56	3.70	.98	1.13	.96	6.28	.89	2.56	0.00
	Rigid	.00	.00	.00	2.80	.22	4.03	9.38	1.28	1.96	2.42	6.86	.94	4.56	0.00
	GVW	1.4	4.2	6.1	37.7	16.1	42.5	74.9	31.8	47.5	76.8	82.5	43.5	81.5	0.0
E Lane1	Num	3	480	416	3	59	16	2	5	45	35	1	1	38	0
	Flex	.00	.00	.00	1.67	.15	.94	.34	.59	.58	.73	.34	.09	.88	0.00
	Rigid	.00	.00	.00	2.38	.15	1.62	1.06	.82	1.00	1.84	.31	.09	2.20	0.00
	GVW	3.3	3.4	5.5	37.4	16.0	32.5	50.5	26.6	37.2	63.5	39.5	27.5	70.0	0.0
W Lane1	Num	5	494	375	5	117	16	2	11	37	59	1	1	15	0
	Flex	.00	.00	.00	1.88	.20	2.56	3.70	.98	1.13	.96	6.28	.89	2.56	0.00
	Rigid	.00	.00	.00	2.80	.22	4.03	9.38	1.28	1.96	2.42	6.86	.94	4.56	0.00
	GVW	1.4	4.2	6.1	37.7	16.1	42.5	74.9	31.8	47.5	76.8	82.5	43.5	81.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2017

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9